

COUNTY	ROOSEVELT	FIELD	Milnesand-SA	STATE	N.M.
OPR	CITIES SERVICE OIL COMPANY				MAP
	3 Government "G"				30-041-10036
	Sec. 8, T-8-S, R-35-E				CO-ORD
	330' fr N Line & 1650' fr W Line of Sec.				
	Spud 8-23-64				CLASS
	Comp 10-28-64				EL 42495
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
9 5/8" 398' 250		Yates 2661			
4 1/2" 4733' 250		Queen 3353			
		SA 3840			
		Slaughter			
		4556			
LOGS EL GR RA IND HC A					
	TD 4734', PBD 4676'				

IP San Andres Perfs 4614-57' Pmpd 50 BOPD + 25 BW. Pot. Based on 24 hr test, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 5050'	TYPE
DATE		

F.R. 7-30-64
PD 5050' - SA

8-24-64 Drlg. 1280' RB

8-31-64 Drlg. 4663'.

9-8-64 TD 4734', PBD 4724', swbg.
Perf @ 4676', 4680', 4684', 4690', 4692', 4696',
4705', 4710' & 4716' W/1 SPI
Ac. 2000 gals.
Swbd 50 BLW, with slight show oil.
Frac 20,000 gals oil + 20,000# sd.
Swbd 42 BLO + 28 BW in 12 hrs.

9-14-64 TD 4734', PBD 4724', pmpg load.
Pmpd 81 BLO + 11 BW in 24 hrs.

9-21-64 TD 4734', PB 4676', ppg. load.
 Perf. @ 4614', 4634', 4642', 4653', 4657',
 w/1 SPF.
 Set BP @ 4676'.
 Ac. 2000 gals.
 Frac. 20,000 gals. oil + 5,000# sd.
 Ppd. 66 BLO/14 hrs. (-257).
9-28-64 TD 4734', PB 4676', ppg. load (-93).
 Ppd. 27 BLO/24 hrs.
10-5-64 TD 4734', PB 4724', WO Pot.
 Ppd. 55½ BO + 20 BFW/48 hrs.
10-12-64 TD 4734', PB 4676', prep to test on pump.
 Ppd. 5 BNO/24 hrs.
 Re-Frac. 20,000 gals. oil + 20,000# sd.
10-19-64 TD 4734', PB 4676', ppg. load (-127).

 Ppd. 75 BLO + 13 BFW/72 hrs.
10-26-64 TD 4734', PB 4676', ppg. load (-10).
11-2-64 TD 4734', PBD 4676', COMPLETED.
