

COUNTY	ROOSEVELT		FIELD	Milnesand-SA		STATE	N.M.	
OPR	CITIES SERVICE OIL COMPANY						MAP	
4 Government "G"								
Sec. 8, T-8-S, R-35-E						CO-ORD		
1980' fr S Line & 660' fr W Line of Sec.								
Spud 9-5-64						CLASS		
Temp. Abd. 10-9-64						EL <u>42442</u>		
			FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING			LOG:					
8 5/8" 426' 200			Yates 2679'					
4 1/2" 4884' 350			Queen 3374					
			SA 3862					
			Slight 4579					
LOGS EL GR RA IND HC A								
			ID 4885', FB 4850'					

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	5000'	TYPE
DATE			

F. R. 9-3-64.
FD 5000' - San Andres.
9-8-64 Dr'g 2690'.
9-14-64 Coring @ 4738'.
Cored 4592-4650', rec. 56' anhy dolo.
w/scatt FPP, sli BO.
Cored 4650-4708', rec. 58' anhy dolo.,
w/scat. FPP, sli bldg. oil.
Cored 4708-27', rec. 19' dolo, bldg. oil,
4718-19'.
9-21-64 ID 4885', FB 4850', swbg.
Cored 4727-85', rec. 58' dolo & anhy.
Bldg. oil 4727-30', 4735-36', 4740-42', 4751-67',
Perf. @ 4656', 4658', 4660', 4666', 4672', 4676',
4679' w/l SFL.
Ac. 2000 gals.
Frac. 20,000 gals. oil + 16,200# sd.
Swbd. 120 BLO/3 hrs.

9-28-64 TD 4885', FB 4850', ppg. load (-303).
 Ppd. 5 BLO + 1½ BW/17 hrs.
10-5-64 TD 4885', FB 4850', ppg. load (-165).
 Ppd. 56 BLO + 32 BFW/48 hrs.
10-12-64 TD 4885', FB 4850', Temp. Abandoned.
 Ppd. 30 BW/24 hrs. (-160).