

COUNTY ROOSEVELT		FIELD Milnesand-SA		STATE N.M.	
OPR CITIES SERVICE OIL COMPANY				MAP	
5 Pate "A"		30-041-10045			
Sec. 7, T-8-S, R-35-E				CO-ORD	
660' fr S Line & 1980' fr E Line of Sec.					
Spud 4-7-64		CLASS		EL 4242	
Comp 5-10-64		FORMATION	DATUM	FORMATION	DATUM
2SG & SX - TUBING		LOG:			
8 5/8" 405' 200		SA 3840			
4 1/2" 4708' 300		Slaughter			
		4567			
LOGS EL GR RA IND HC A					
TD 4709', PBD 4684'					

IP San Andres Perfs 4588-4671' Pmpd 71 BOPD + 13 BW. Pot.
Based on 24 hr test, Gravity 28., GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH 4700'	TYPE
DATE		

F.R. 4-9-64
PD 4700' - SA
Contractor - Cactus Drlg. Co.
4-13-64 Drlg. 4215'.
4-20-64 TD 4709', PBD 4705', prep to swab.
Perf @ 4690', 4697' & 4700' W/1 SPI.
4-27-64 TD 4709', PBD 4684', RU Pump.
Swbd dry 4690-4700'
Att. to Ac., would not take
Re-Perf @ 4690', 4697', & 4700' W/1 SPI
Ac. 1000 gals. 4690-4700'
Swbd load & swbd 1 B Salt Wtr PH.
Set retainer @ 4684' & squeezed perfs
4690-4700' W/49 sx.
Perf @ 4588', 4605', 4612', 4635', 4640',
4646', 4649', 4663' & 4671' W/1 SPI
Ac. 2000 gals.
Frac 20,000 gals oil + 20,000# sd. 4588-4671'

4-27-64 - cont. -
Swbd 36 BLO/4 hrs.
5-4-64 TD 4709', PBD 4684', pmpg load.
Pmpd 22 BLO + 18 BW/8 hrs. (-254 BLO).
5-11-64 TD 4709', PBD 4684', COMPLETED.