

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
LC-062178

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- WIW	7. Unit Agreement Name Milnesand Unit
2. Name of Operator Breck Operating Corp.	8. Farm or Lease Name
3. Address of Operator P.O. Box 911, Breckenridge, Texas 76024	9. Well No. 136
4. Location of Well UNIT LETTER H, 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 8-S RANGE 35-E NMPM.	10. Field and Pool, or Wildcat Milnesand (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 4220' GR	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above mentioned well is plugged and abandoned, and the wellsite is ready for final inspection. The plugs were placed as follows:

1. CIBP @ 4510' w/10 sx on top-CIBP Tagged.
2. 60 sx 512-330'-4½" casing shot @ 474' and pulled. Top of plug tagged.
3. 10 sx 30-3'-Cement circulated. Cut 8 5/8" 3' below surface and welded on steel plate.

Hole loaded with brine and salt gel.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Kevin G. Duncan TITLE Petroleum Engineer DATE 5-11-87

APPROVED BY [Signature] TITLE OIL & GAS INSPECTOR DATE JUL 8 1987  
CONDITIONS OF APPROVAL, IF ANY: