

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O.C.C.

JUN 16 2 42 PM '64

WELL RECORD

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRORATION OFFICE	
OPERATOR	

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Cities Service Oil Company

Pate A

(Company or Operator)

(Lease)

Well No. 6, in SE $\frac{1}{4}$ of NE $\frac{1}{4}$, of Sec. 7, T. 8S, R. 35E, NMPM.Milnesand San Andres

Pool,

Roosevelt

County.

Well is 1980 feet from North line and 660 feet from East lineof Section 7. If State Land the Oil and Gas Lease No. is -.Drilling Commenced May 13, 19 64 Drilling was Completed May 24, 19 64.Name of Drilling Contractor Cactus Drilling CompanyAddress San Angelo, TexasElevation above sea level at Top of Tubing Head 4241. The information given is to be kept confidential until-, 19 -.

OIL SANDS OR ZONES

No. 1, from 4630 to 4669 No. 4, from - to -No. 2, from - to - No. 5, from - to -No. 3, from - to - No. 6, from - to -

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from - to - feet.No. 2, from - to - feet.No. 3, from - to - feet.No. 4, from - to - feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
<u>8-5/8"</u>	<u>24#</u>	<u>New</u>	<u>413</u>	<u>Larkin</u>			
<u>4 1/2"</u>	<u>9.5#</u>	<u>New</u>	<u>4710</u>	<u>Larkin</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>11"</u>	<u>8-5/8"</u>	<u>424</u>	<u>200</u>	<u>Plug</u>		
<u>7-7/8"</u>	<u>9.5#</u>	<u>4721</u>	<u>350</u>	<u>Plug</u>		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized w/2000 gallons LST and 15 ball sealers,Fraced w/20,000 gallons gelled lease crude and 2000# sand.

Result of Production Stimulation

Pumped 80.40 bbls. oil and 32 bbls. water in 24 hrs.Depth Cleaned Out 4680

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4724 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing June 13 64, 19
OIL WELL: The production during the first 24 hours was 112.40 barrels of liquid of which 71.53 % was oil; 0 % was emulsion; 28.47 % water; and 0 % was sediment. A.P.I. Gravity 29°
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy..... 2118	T. Devonian.....	T. Ojo Alamo.....	
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....	
B. Salt..... 2673	T. Montoya.....	T. Farmington.....	
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....	
T. 7 Rivers.....	T. McKee.....	T. Menefee.....	
T. Queen..... 3367	T. Ellenburger.....	T. Point Lookout.....	
T. Grayburg.....	T. Gr. Wash.....	T. Mancos.....	
T. San Andres..... 3850	T. Granite.....	T. Dakota.....	
A Zone 4569	T.	T. Morrison.....	
T. Glorieta.....	T.	T. Penn.....	
T. Drinkard.....	T.	T.	
T. Tubbs.....	T.	T.	
T. Abo.....	T.	T.	
T. Penn.....	T.	T.	
T. Miss.....	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1175	1175	Red Bed				
1175	2008	833	Red Bed & Anhy.				
2008	3344	1336	Anhy & Salt				
3344	3776	432	Anhy & Gyp				
3776	3910	134	Anhy & Dolomite				
3910	4720	810	Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 16, 1964
Company or Operator Cities Service Oil Company Address Box 69, Hobbs, New Mexico
Name Position or Title District Clerk