
Form 9-331a (Feb. 1951) MOV 20 1962

(SUBMIT IN TRIPLICATE)

E. W. STANDLEY DISTRICT ENGINEER

UNITED STATES

DEPARTMENT OF THE INTERIOR SEEDEGICAL SURVEY 52



CONTROL HER REPORT

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

•			•		November 26	962
Well No. 1 Fumble	Federal is located	1980	ft. from	line and bod ft.	from W line of sec. 3	4
NW SW 34		85	37E	MMM	,	
(1/ Sec. and Sec. No.	)	(Twp.)	(Range)	(Meridian)	)	
Allison Per	en .		Roosevel	t	New Mexico	
(Field)			(County or Subdivi	sion)	(State or Territory)	
The elevation of the	derrick floo	r abov	e sea level is .	ft.		

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment-was proposed to drill to a total depth of approximately 9750 feet with rotary tools and complete in the Bough "C" formation. The casing program will be as follows:

10-3/4 inch 32.75%, H-40 surface casing to be set @ 400 feet and comented with

400 sacks. Cement will be circulated to surface. 7-5/8 inch 26%, J-55 casing set @ 4250 feet and comented with 450 sacks cament. 4-1/2 11.60% N-80 casing set @ 9750 feet and cemented with 400 sacks.

l understand	that this plan of work must receive approval	in writing by the Geological Survey before operations may be commenced.
Company	DOB Oil Properties, Inc	!•
Address	Box 953	
	Midland, Texas	By Terred Huif
		Title
		GPO 862040