

District I
1525 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Frio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-041-10057
5. Indicate Type of Lease
STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other ☒ INJECTION

2. Name of Operator
J. CLEO THOMPSON

3. Address of Operator
325 N. ST. PAUL, SUITE 4300, DALLAS, TX 75201

7. Lease Name or Unit Agreement Name:
MILNESAND UNIT

8. Well No. 187

9. Pool name or Wildcat
MILNESAND (SAN ANDRES)

4. Well Location

Unit Letter B 660 feet from the NORTH line and 1980 feet from the EAST line

Section 18 Township 8S Range 35E NMPM County ROOSEVELT

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
4238' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: REPAIRED INJECTION WELL ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1.) RU. POOH W/TBG & OLD PACKER. RIH W/BIT & SCRAPER TO BOTTOM & CLEAN OUT 4711'.
- 2.) RIH W/2 7/8" X 4 1/2" PERMANENT PACKER WITH BLANKING PLUG AND SET @ 4477'.
- 3.) RIH W/2 7/8" 6.5#/FT J-55 & N-80 TBG WITH SEAL ASSY AND STINGER ON END.
- 4.) CIRCULATE 250 SX CLASS C CEMENT BETWEEN 2 7/8" AND 4 1/2" CASING & UPON FLUSHING LATCH 2 7/8" TBG IN PACKER. CIRCULATE 81 SX S TO PIT.
- 5.) RIH W/2 1/16" X 2 7/8" INJECTION PACKER ON 2 1/16" PC TBG AND SET PACKER @ 4433'.
- 6.) CIRCULATE PACKER FLUID. SET PACKER. AND TEST ANNULUS TO 500 PSI. & RETURN WELL TO INJECTION. (4 1/2" 10.5# @ 4720'. PERFS 4575-4658')

NOTE: ORIGINAL CHART HANDED TO BILLY PRITCHARD ON LOCATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. Stevens TITLE ENGINEER DATE 12/07/00
Type or print name JIM STEVENS Telephone No. (915)366-8886

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____
Conditions of approval, if any: