
COPY TO U. U. gen (L.

Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

PLICATE)	Lease No. 16-060978
HE INTERIOR	MAY 2 5 75
•	W. 1. 1

U. 5 (5.5)

SUNDRY NOTICES AND RE	
OTICE OF INTENTION TO CHANGE PLANS	UENT REPORT OF WATER SHUT-OFF
SUBSEQ	UENT REPORT OF RE-DRILLING OR REPAIR
SUBSEC	WENT REPORT OF ABANDONMENT
OTICE OF INTENTION TO PULL OR ALTER CASING	MENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK NATURE OF F	REPORT, NOTICE, OR OTHER DATA)
(112)	Mary 21 1963
	e and 624.3 ft. from W line of sec. 19
M/4 Nu/4 Sec. 19 88 35 E (Range)	(Meridian)
(V Sec. and Sec. No.) (Twp.)	Fer Herres
(Field) (County or Subdivision) (State or Territory)
DETAILS OF	WORK
DETAILS OF tate names of and expected depths to objective sands; show sizes, weights, ing points, and all other import 5/10/63: Perforated 4610-16, 4622-26, 462 4672-79, 4682-88 with 2 jet shote per foot 250 gallone 15% DS-30 and, treating press	WORK and lengths of proposed casings; indicate mudding jobs, cemerant proposed work) 8-32, 4634-46, 4663, 4666-68, Treated thru 2" tubing with mre 2400f 8 2.5 BPK. 1/2" casing with 750 gallone 1 20,000f 20/40 send using 60
DETAILS OF tate names of and expected depths to objective sands; show sizes, weights, ing points, and all other import 5/10/63: Perforated tolo-16, \$622-26, \$62 1572-79, \$662-88 with 2 jet shote per foot 250 gallons 15% DS-30 and, treating press 5/11/63: Pulled tubing and treated down to DS-30 acid, 20,000 gallons refined oil and ball scalars. Harimum pressure \$200f & 15 I understand that this plan of work must receive approval in writing by Company El Chorro Exploration, Inc.	work and lengths of proposed casings; indicate mudding jobs, ceme ant proposed work) 8-32, 4634-46, 4663, 4666-68, Treated thru 2" tubing with are 2400f 8 2.5 BPK. 1/2" casing with 750 gallons 120,000f 20/40 send using 60 1.2 BPK. the Geological Survey before operations may be commenced.
DETAILS OF tate names of and expected depths to objective sands; show sizes, weights, ing points, and all other import 5/10/63: Perforated tolo-16, 4622-26, 462 1572-79, 4682-88 with 2 jet shote per foot 250 gallons 15% DS-30 acid, treating press 5/11/63: Pulled tubing and treated down to DS-30 acid, 20,000 gallons refined oil and ball scalars. Harimum pressure \$200f & 15 I understand that this plan of work must receive approval in writing by Company El Chorro Exploration, Inc.	work and lengths of proposed casings; indicate mudding jobs, ceme ant proposed work) 2-32, 4634-46, 4663, 4666-68, Treated thru 2" tubing with are 2400f 6 2.5 BPM. 1/2" casing with 750 gallone 1 20,000f 20/40 send using 60 1.2 BPM. the Geological Survey before operations may be commenced.
1 understand that this plan of work must receive approval in writing by 1 understand that this plan of work must receive approval in writing by Company El Chorro Exploration, Inc. Address 6/0 011 Reports & Gas Services	work and lengths of proposed casings; indicate mudding jobs, ceme ant proposed work) 8-32, 4634-46, 4663, 4666-68, Treated thru 2" tubing with are 2400f 8 2.5 BPK. 1/2" casing with 750 gallone 120,000f 20/40 send using 60 1.2 BPK. the Geological Survey before operations may be commenced.