

Form 9-331a  
(Feb. 1951)

APPROVED

(SUBMIT IN TRIPLICATE)

	X	

SEP 16 1963

UNITED STATES

J. L. GORDON

DEPARTMENT OF THE INTERIOR  
ACTING DISTRICT ENGINEER GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. LC-060978

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<b>X</b>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 13, 1963

**Jacobs Federal**  
Well No. 12 is located 1980 ft. from [N] line and 1980 ft. from [E] line of sec. 19

34/4 NE/4 Sec. 19 2 S 35 E 10PM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Undesignated (Milnesand-3A) Roosevelt New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Cemented new 4 1/2" 10.5# J-55 casing at 4735, total depth, with 200 sacks Halliburton class C cement. Plug down 6:35 A. M. 9/12/63. MOC 24 hours and pressure tested casing with 1,000# for 30 minutes, test O.K.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company E1 Chorro Exploration, Inc.Address c/o Oil Reports & Gas ServicesBox 763Hobbs, New MexicoBy A. L. SmithTitle Agent