

COUNTY	ROOSEVELT	FIELD	Milnesand	STATE	NM
OPR	GULF OIL CORPORATION				MAP
1 Brown-Federal "A"					CO-ORD
Sec. 4, T-8-S, R-35-E					4229
1980' fr N & W Lines of Sec.					
Spud 11-2-64					CLASS
Comp 3-29-65					E
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
8 5/8" 442' 250		Rust 2168			
4 1/2" 4803' 450		Yates 2653			
		Queen 3354			
		SA 3829			
LOGS EL GR RA IND HC A					
		TD 4803', PBD 4708'			

IP San Andres Perfs 4552½-4635½' Pmpd 6 BOPD + 19 BW. Pot.
Based on 24 hr test, gravity 27.8, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co. PROP DEPTH 4800' TYPE
DATE

11-9-64 F.R. 11-5-64
11-16-64 PD 4800' - SA
11-23-64 Contractor - Cactus Drlg. Co.
Drlg. 4001' anhy.
TD 4803', WOC.
TD 4803', PBD 4708', swbg.
Perf 4784-89' W/4 SPF
Ac. 500 gals.
Swbd 1.37 BWPH, w/no shows.
Squeezed perfs 4784-89' W/50 sx.
Perf 4552½-55½', 4596½-99½', 4612½-15½',
4632½-35½' W/2 SPF
Ac. 2500 gals.
Swbd 20 BW + 56 BAW, w/tr. oil in 10 hrs.

11-30-64 TD 4803', PBD 4708', prep to test on pump.
Frac 20,000 gals oil + 20,000# sd.
Swbd 4 BLO + 35 BW in 5 hrs.
12-7-64 TD 4803', PBD 4708', pmpg load.
Pmpd 46.75 BF (12% LO, 54% wtr, 34% gel) in
24 hrs (-587 BLO).
12-14-64 TD 4803', PBD 4708', SD Pump Repairs.
Pmpd 28.87 BF (27% LO, 73% wtr) in 24 hrs.
12-21-64 TD 4803', PBD 4708', pmpg load.
Pmpd 24.75 BF (36% LO, 64% wtr) in 24 hrs.
(-491 BLO).
1-4-65 TD 4803', PBD 4708', SD Repairs.
Pmpd 26 BF (14% LO, 86% wtr) in 24 hrs.
(-472 BLO).

1-11-65 TD 4803', PBD 4708', pmpg load.
Pmpd 38.5 BF (30% LO, 70% FW) in 24 hrs.
(-432 BLO).
1-18-65 TD 4803', PBD 4708', SD Pump Repairs.
Pmpd 23.37 BF (22% LO, 78% FW) in 24 hrs
(-421 BLO).
1-25-65 TD 4803', PBD 4708', SD Pump Repairs.
Treated w/500 gals paraffin solvent +
3000 gals kerosene 4552½-4635½'.
Pmpd 99 BLO + 28½ BW in 72 hrs.
2-1-65 TD 4803 , PBD 4708', pmpg load.
Pmpd 52 BLO + 37 BW in 67 hrs (-316 BLO).
2-8-65 TD 4803', PBD 4708', pmpg load.
Pmpd 13.75 BLO + 15.7 BW in 24 hrs (-219 BLO).

2-15-65 TD 4803', PBD 4708', pmpg load.
Pmpd 46.75 BF in 24 hrs (56% LO, 44% Wtr)
(-159 BLO).
2-19-65 TD 4803', PBD 4708', pmpg load.
Pmpd 11 BLO + 27 BW in 24 hrs (-94 BLO).
3-1-65 TD 4803', PBD 4708', pmpg load.
Pmpd 17 BLO + 65 BFW in 72 hrs (-40 BLO).
3-5-65 TD 4803', PBD 4708', pmpg load.
Re-Ac. 1000 gals. 4552½-4635½'.
Pmpd 38½ BW in 24 hrs.
3-15-65 TD 4803', PBD 4708', tstg on pump.
Pmpd 13 BNO + 35 BW in 72 hrs.
3-22-65 TD 4803', PBD 4708', tstg on pump.
Pmpd 10 BNO + 57 BW in 72 hrs.
3-29-65 TD 4803', PBD 4708', tstg on pump.

4-5-65 Pmpd 10 ENO + 50 BW in 72 hrs.
TD 4803', PBD 4708', COMPLETED.