

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

MAR 2 1 37 PM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Tom L. Ingram		8. Farm or Lease Name Wilson
3. Address of Operator P. O. Box 1757 - Roswell, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER M 554 FEET FROM THE South LINE AND 766 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 8-S RANGE 38-E NMPM.		10. Field and Pool, or Wildcat North Sawyer Devonian
11. Elevation (Show whether DF, RT, GR, etc.) 3966.6 GR		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 8-5/8" Casing at 4200' as follows:

2356.80', 77 joints, 8-5/8" 32# J-55 ST&C
1863.16', 60 joints, 8-5/8" 24# J-55 ST&C

Cemented with 300 sacks 50/50 Posmix plus 6% gel and 200 sacks Neat. Top of cement by survey 4100' inside the pipe, 3000' outside. Tested casing to 1000 psi for 30 minutes, held okay. WOC 36 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Tom L. Ingram TITLE Owner DATE 3-1-65

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: