

COUNTY <u>Roosevelt FIELD</u> <u>Milnesand-San Andres</u> STATE <u>N.M.</u> NO. <u> </u>									
OPR. <u>Lario Oil & Gas Company</u> MAP <u> </u>									
NO. <u>4</u> LEE Federal "A" <u>3D-041-10090</u>									
SEC. <u>14</u> T. <u>8S</u> BLK. <u>34E</u> SUR. <u> </u> CO-ORD. <u> </u>									
LOC. <u>660' fr S Line & 1980' fr E Line of Sec.</u>									
MI. <u> </u> FROM <u> </u> CLASS. <u> </u> EL. <u>3266.8</u>									
SPUD. <u>12-8-63</u> COMP. <u>1-1-64</u> FORMATION <u> </u> DATUM <u> </u> FORMATION <u> </u> DATUM <u> </u>									
IRI. <u> </u> LOG. <u> </u>									
<u> </u> Yates 2608									
CSG. & SX. <u> </u> SA 3784									
<u>8 5/8" 375' 200</u> SA Poro									
<u>4 1/2" 4680' 200</u> 4531									
<u> </u>									
TBG. DEPTH SIZE									
LOGS EL GR RA IND HC A									
<u> </u> ID 4680' PB									
PROD INT. (DAILY RATE) BS&W GH GOR GTY C. P. T. P. HRS. TEST									
<u>4586-4630' Flwd 59 RO 22/64" 29.1 840# 660# 24</u>									
<u>(San Andres)</u>									
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.									
CONT. <u>Verna Drilg. Co.</u> PROP DEPTH <u>4700'</u> TYPE <u> </u>									
DATE <u> </u>									

F.R. 12-5-63
 PD 4700' - SA
 12-9-63 ID 376' RE, WOC.
 12-16-63 Trlg 4571' 1m.
 12-30-63 ID 4680', flwg load.
 Perf @ 4586', 4589', 4591', 4603', 4608', 4612',
 4625', & 4630' W/1 SPI
 Ac. 2000 gals
 Frac 20,000 gals oil + 30,000# sd.
 Flwd 60 BLO/24 hrs thru 22/64" chk., CP 950#,
 TP 750#. (-211 BLO).
 1-6-64 ID 4680', tstg.
 Load recovered
 1-13-64 ID 4680', COMPLETED.