

COUNTY ROOSEVELT		FIELD Milnesand-San Andres		STATE N.M.	
OPR MAXWELL OIL COMPANY				MAP	
3 Fraser					
Sec. 6, T-8-S, R-35-E				CO-ORD	
660' fr S Line & 1980' fr E Line of Sec.					
Spud 3-20-64				CLASS	
Comp 4-13-64				EL 4260'	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
		Yates 2644			
8 5/8" 370' 225		Queen 3334			
4 1/2" 4637' 300		SA 3814			
		Slaughter			
		4526			
LOGS EL GR RA IND HC A					
		TD 4637', PBD 4628'			

IP San Andres Perfs 4532-4618' Flwd 69 BO. Pot. Based on 24 hr test thru 18/64" chk., TP 435#, CP 655#, gravity 30.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Monarch Drlg. Co.	PROP DEPTH 4650'	TYPE
DATE		

	F.R. 3-12-64
	PD 4650' - SA
	contractor - Monarch Drlg. Co.
3-23-64	Drlg. 1970'.
3-30-64	Drlg. 4450'.
4-6-64	TD 4637', flwg load.
	Perf @ 4532', 4539', 4544', 4552', 4562', 4570',
	4577', 4585', 4594', 4602', 4608' & 4618' W/1
	SPI
	Ac. 2000 gals.
	Frac 30,000 gals oil + 30,000# sd.
4-13-64	TD 4637', PBD 4628', tstg. on pump.
4-20-64	TD 4637', PBD 4628', COMPLETED.
	Flwd 35 BNO in 24 hrs thru 24/64" chk.