

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY TO O. C. C.
SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 068124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McClellan Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Todd Upper San Andres

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

Sec. 28-7S-35E

12. COUNTY OR PARISH

Roosevelt

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

FRANKLIN, ASTON & FAIR, INC.

3. ADDRESS OF OPERATOR

P. O. Box 1090, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface660' FNL & 660' FEL of Section 28, Township 7 South,
Range 35 East

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4242' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was completed October 21, 1963, as a gas producer from perforations 4140' to 4210' in the Todd San Andres A zone. The TD was 4570' and 5 $\frac{1}{2}$ " casing was set at 4355'. The San Andres B zone was perforated from 4241' to 4274' acidized and swabbed dry. A bridge plug at 4230' separates the upper set of perforations from the lower set. Production has declined until it is no longer economical to produce this well. Pursuant to telephone conversations with Mr. Gordon at the U.S.G.S. office in Hobbs, we plan to P & A this well as follows:

25 sack cement plug spotted VIA tubing on top of bridge plug and across perms 4140' to 4210'.

25 sack plug at top of San Andres 3450'.

25 sack plug at base of 8 5/8" surface casing at 271'.

10' plug and marker at surface.

The 5 $\frac{1}{2}$ " casing will be left in the hole. This work is planned for August 19, 1971.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Geologist

DATE August 19, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 20 1971

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED

AUG 2 1971

OIL CONSERVATION COMM.
WASHINGTON, D.C.