

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPL  
(Other instructions  
verse side)Form approved.  
Budget Bureau No. 42-B1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 065510

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 22

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Todd San Andres

11. SEC. T., R., M., OR BLK. AND  
SURVEY OR AREA

22-T7S- R35E

12. COUNTY OR PARISH

Roosevelt

13. STATE

N.M.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER  
WELL WELL2. NAME OF OPERATOR  
Jack L. McClellan3. ADDRESS OF OPERATOR  
P.O. Box 8484 Roswell, N.M. 882014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FSL and 1650' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4208.5 GL

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

on Feb 20, 1970, this well was plugged and abandoned as follows:

Cemented with 25 sacks from 4100' to 3800', set 10 sack plug from 1900'  
to 2050' inside 4 1/2" casing. Shot casing off at 997', spotted 30 sack  
plug from 1025' to 900', 1/2 in & 1/2 out of 4 1/2" Casing. Set 30 Sack plug  
from 300 to 200', 1/2 in and 1/2 out 8 5/8" surface csg. Set 10 Sack plug in  
top of surface casing, installed dry hole marker. Recovered total 997'  
4 1/2" casing.

Casing Pullers, Inc performed the above operation.

18. I hereby certify that the foregoing is true and correct

SIGNED

*John L. Gordon*

TITLE Production Supt.

DATE 2-23-70

(This space for Federal or State use only)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAY 2 1970

\*See Instructions on Reverse Side J. L. GORDON  
ACTING DISTRICT ENGINEER

RECEIVED

JUN 2 1970

OIL CONSERVATION COMM.  
HOBBS, N. M.