I M. OIL CONS. COMMISSION P. O. BOX 1980 Form 9-331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Form Approved. Budget Bureau No. 42–R1424 5. LEASE NM 0145685 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1. oil X gas well well other	Horton Federal 9. WELL NO.
2. NAME OF OPERATOR Amoco Production Company	2 10. FIELD OR WILDCAT NAME
 3. ADDRESS OF OPERATOR P. O. Box 68, Hobbs, New Mexico 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 330' FNL X 1650' FWL, Unit C AT TOP PROD. INTERVAL: Sec. 30, T-8-S, R-35-E AT TOTAL DEPTH: 	AREA 30-8-35 12. COUNTY OR PARISH Lea NM
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
 (other) Revise Plans X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent. 	irectionally drilled give subsurface leasting and
Propose to expose Zone VI pay and remove sca Form 9-331 dated 6-21-82). Pull rods, pump with 50-55' tailpipe below the packer. Set possible. Pump 5 drums of Visco 4948 scale Flush with 3 bbls water. Lower and set pac	ale as follows: (This revises , and tubing. Run a workstring the tailpipe as near to TD as converter with 13 bbls water. ker within 5' of TD. Acidize with
1000 gal 15% LST NE HCL with 1 gal/1000 corn water. Pull workstring and packer. Set a m 4676'-89' RDB. Set a packer approx. 30' abo gal 5% LST NE HCL with 1 gal/1000 corrosion water. Pull the retrievable bridge plug and tubing. Return well to production.	rosion inhibitor. Flush with 20 bb retrievable bridge plug between ove perfs. Acidize with 1000 n inhibitor. Flush with 20 bbls
0+4-USGS , R 1-HOU 1-SUSP 1-CLF Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct SIGNED Cathy L. Farman TITLE ASt. Adm. Ana	Set @ Ft.
APPROVED (This space for Federal or State office APPROVED (This space for Federal or State office CONDITIONS OF APPROVAL, IF ANY: JUL 2 3 1982	
JUL 2-3 1902 FOR JAMES A. GILLHAM DISTRICT SUPERVISOR	Ide U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

0.000 HO333 OMICE

L.

.

JUL 27 1982