

N. M. OIL CONS. COMMISSION  
P. O. BOX 1980  
HOBBS, NEW MEXICO 88240

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 330' FNL X 1650' FWL, Unit C  
AT TOP PROD. INTERVAL: Sec. 30, T-8-S, R-35-E  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☒  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

**RECEIVED**  
JUN 21 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM 0145685  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Horton Federal  
9. WELL NO.  
2  
10. FIELD OR WILDCAT NAME  
Milnesand San Andres  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
30-8-35  
12. COUNTY OR PARISH  
Lea  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4229' RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Propose to expose Zone VI pay and remove scale as follows: Pull rods, pump, and tubing. Run a workstring and 4 joints of tailpipe below packer. Set packer so that bottom of workstring is within 1 ft. of the packer assembly at 4683' rotary drive bushing (RDB). Pump 4 drums of Visco 4948 scale converter with 11 bbls. water. Flush with 5 bbls. water. Acidize with 1000 gal 15% LST NE HCL containing 1 gal/1000 corrosion inhibitor. Flush with 20 bbls. water. Pull workstring and packer, and retrieve the packer assembly at 4683' RDB. Tag TD for fill and clean out if necessary. Run a workstring with 1 joint of tailpipe and set the packer between 4676' and 4689' RDB. Pump 4 drums of Visco 4948 scale inhibitor with 11 bbls. water. Flush with 5 bbls. water. Acidize with 1000 gal 15% LST NE HCL containing 1 gal/1000 corrosion inhibitor. Flush with 20 bbls. water. Pull workstring and packer. Run rods, pump, and tubing. Return well to production. (Verbal approval by Peter Chester 6-18-82).  
0+4-USGS,R 1-HOU 1-SUSP 1-CLF

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy L. Forman TITLE Ast. Adm. Analyst DATE 6-21-82

APPROVED BY (Orig. & 4) PETER W. CHESTER (This space for Federal or State office use)  
CONDITIONS OF APPROVAL, IF ANY:

DATE \_\_\_\_\_

JUN 23 1982

FOR  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

RECEIVED

JUN 24 1982

RECEIVED

CHIEF  
HOBBS OFFICE