

COUNTY	ROOSEVELT FIELD Milnesand-San Andre STATE N.M.			
OPR	PAN AMERICAN PETROLEUM CORPORATION			MAP
3 Horton, Russell E. Federal				
Sec. 30, T-8-S, R-35-E			CO-ORD	
1650' fr N Line & 330' fr W Line of Sec.				
Spud 3-26-64		CLASS EL 4229'		
Comp 4-15-64		FORMATION	DATUM	FORMATION
CSG & SX - TUBING		LOG:		
8 5/8"	397'	200	Anhy 2176	
4 1/2"	4695'	200	Yates 2683	
			SA 3894	
LOGS EL GR RA IND HC A				
TD 4695', PBD 4693'				

IP San Andres Perfs 4650-68' Flwd 70 BOPD + 4 BW. Pot. Based on 24 hr test thru 15/64" chk., gravity 30., GOR 897. TP 180#.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	4700'	TYPE
DATE			

F.R. 3-26-64; Oper's Elev. 4229' PD
PD 4700' - SA
3-30-64 Drlg. 3240'.
4-6-64 TD 4695', reaming.
Cored 4595-4645', rec 50' dns down, w/NS.
Cored 4645-4695', rec 50' anhy. solo., w/good
vugular poro. & scatt. BO&G 4652-43'.
4-13-64 TD 4695', PBD 4693', flwg load.
Perf 4650-68' W/2 SPF
Ac. 500 gals.
Frac 20,000 gals oil - 20,000 gals.
Flwd 60 BLO/5 hrs thru 20/64" chk.
4-20-64 TD 4695', PBD 4693', COMPLETED.
(Holding for tops & core descriptions)
4-27-64 TD 4695', PBD 4693', Completion Reported.