

COPY TO O. C. C.

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Injection  
well well2. NAME OF OPERATOR  
Amoco Production Company3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 900' FSL X 1650' FWL, Sec. 30  
AT SURFACE: (Unit N, SE/4 SW/4)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Convert to injection ☒☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

APR 11 1980

E: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO5. LEASE  
NM-0145685

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Horton Federal9. WELL NO.  
12

10. FIELD OR WILDCAT NAME

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
30-8-3512. COUNTY OR PARISH  
Roosevelt13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4226' RDB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in service unit 1/21/80. Laid down rods. Ran packer and tubing to 4755'. Spotted 80 gallons 15% NEFE acid. Raised and set packer at 4520'. Acidized with 5000 gallons 15% NEFE acid in 2 stages separated with 250# rock salt in 300 gallons gelled brine water. Flushed with 22 bbls lease water. Pulled packer and laid down tubing. Ran 2-3/8" plastic coated tubing and packer. Packer set at 4611'. Water injection commenced 3/5/80.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Marty K. Stos TITLE Asst. Admin. Anal. DATE 4/9/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

0 + 4 USGS-H 1-Hou 1-Susp 1-MKE

ACCEPTED FOR RECORD

APR 11 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side