

COUNTY ROOSEVELT FIELD Milnesand-San Andres STATE N.M.

OPR PAN AMERICAN PETROLEUM CORPORATION

MAP

1 Rogers, Ruth E.

Sec. 25, T-8-S, R-34-E

CO-ORD

660' fr N Line & 1980' fr W Line of Sec.

Spud 4-17-64

CSG & SX - TUBING	CLASS				EL
	FORMATION	DATUM	FORMATION	DATUM	
	LOG:				42432
3 5/8" 401' 200	Rust 2158				
4 1/2" 4696' 200	Yates 2680				
	SA 3904				
LOGS EL GR RA IND HC A					
	TD 4696'				

TEMPORARILY ABANDONED

30-041-10124

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.

PROP DEPTH 4700'

TYPE

DATE

F.R. 4-9-64; Oper's Elev. 4245' RDB
PD 4700' - SA
Contractor - Cactus Drlg. Co.
-20-64 Drlg. 2930'.
4-27-64 TD 4696', WOC.
Cored 4605-57', rec 52' being:
10' dense gry anhy. dolo; 3' dns gry anhy.
dolo., w/scatt. vuggy poro., NS; 33' dns
gry anhy. dolo; 6' gry dolo., w/PPP & scatt.
horiz. fracs., bldg. oil.
Cored 4657-96', rec 39' gry dolo., w/scatt.
PPP, horiz. & vert. fracs., bldg. oil.
-4-64 TD 4696', PBD 4691', RU Pump.
Perf 4645-54', 4655-64', 4672-86' W/2 SPF
Ac. 500 gals.
Frac 20,000 gals oil.
Swbd 135 BLO + 11 BW/14 hrs.
5-11-64 TD 4696', PBD 4691', pumping load.
Pmpd 22 BLO + 59 BW/72 hrs.

5-18-64 TD 4696', PBD 4691', pmpg load.
Pmpd 22 BLO + 62 BW/72 hrs.

5-25-64 TD 4696', PBD 4691', pmpg load.
Pmpd 6 BLO + 45 BW/48 hrs.

6-1-64 TD 4696', PBD 4692', tstg. on pump.
Squeezed perfs 4645-86' W/75 sx.
DO to 4692'.
Re-Perf 4682-87' W/2 SPF
Ac. 1000 gals.
Pmpd 114 BLO + 24 BLW & 36 BNW in 52 hrs.

6-8-64 TD 4696', PBD 4692', tstg.
Pmpd 251 BW/72 hrs.

6-15-64 TD 4696', PBD 4692', tstg.
Pmpd 298 BW/72 hrs.

6-22-64 TD 4696', PBD 4692', TEMPORARILY ABANDONED.
Pmpd 100 BW/24 hrs.

COUNTY	ROOSEVELT	FIELD	Milnesand-SA	STATE	N.M.	OWDD
OPR	PAN AMERICAN PETROLEUM CORPORATION					MAP
1 Rogers, Ruth E.						
Sec. 25, T-8-S, R-34-E					CO-ORD	
660' fr N Line & 1980' fr W Line of Sec.						
Re-Spud 8-20-64			CLASS		OWDD 10 412438	
Temp. Abd. 9-2-64		FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING						
8 5/8"	401'	200				
4 1/2"	4696'	200				
LOGS EL GR RA IND HC A						
		TD 4766'				

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4800'	TYPE RT
DATE		

10-26-64 F.R.C. 10-30-64, OWDD, OTD 4696'
Orig. Temp Abd 6-18-64
TD 4766', TEMPORARILY ABANDONED.
Squeezed perfs 4682-87' W/100 sx.
Deepened 4696-4738'
Ac. 500 gals. (OH 4696-4738')
Swbd wtr.
Deepened 4738-4766'
Ac. 500 gals. (OH 4696-4766')
Swbd 14 BLW + 29 BFW/14 hrs.
Re-Ac. 500 gals. (OH 4696-4766')
Swbd 59 BFW, with tr. oil in 14 hrs.