

COUNTY	ROOSEVELT		FIELD	Milnesand-SA		STATE	N.M.		
OPR	PAN AMERICAN PETROLEUM CORPORATION						MAP		
7 Horton, Russell E.-Federal									
Sec. 30, T-8-S, R-35-E						CO-ORD			
330' fr N Line & 2241' fr E Line of Sec.									
Spud 6-19-64			CLASS			EL 4224'			
Comp 7-8-64			FORMATION	DATUM	FORMATION	DATUM			
CSG & SX - TUBING 8 5/8" 412' 225 4 1/2" 4696' 200			LOG:						
			SA	3892					
LOGS EL GR RA IND HC A									
			TD 4696', PBD 4693'						

IP San Andres Perfs 4674-88' Flwd 279 BOPD. Pot. Based on 5 hr test of 58 BO thru 18/64" chk., TP 700#, CP 400#, gas oil ratio 1850.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH	4700'	TYPE
DATE			

F.R. 5-28-64; Oper's Elev. 4226' KB, Oper's PD 4700' - SA
Contractor - Cactus Drlg. Co.
6-22-64 Drlg. 2225'.
6-29-64 TD 4696', running logs.
7-6-64 TD 4696', prep to frac.
Perf 4674-88' W/2 SPF
7-13-64 TD 4696', PBD 4693', COMPLETED.
Ac. 500 gals.
Frac 20,000 gals oil.