

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

OCT 11 10 08 AM '65

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>1-1369</b>
7. Unit Agreement Name <b>-</b>
8. Farm or Lease Name <b>None</b>
9. Well No. <b>4</b>
10. Field and Pool, or Wildcat <b>Chavezco- San Andres</b>
12. County <b>Huerfano</b>

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator <b>Skelly Oil Company</b>
3. Address of Operator <b>Box 730 - Hobbs, New Mexico</b>
4. Location of Well UNIT LETTER <b>0</b> , <b>640</b> FEET FROM THE <b>South</b> LINE AND <b>1900</b> FEET FROM THE <b>East</b> LINE, SECTION <b>33</b> TOWNSHIP <b>4 T-S</b> RANGE <b>33-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>4525' DF</b>

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

### SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached total depth of 4525' on September 26, 1965. Set 241 jts (4524.5) of new 4-1/2" OD 10.5# DR 80 J-55 RT & C casing at 4524', and cemented with 350 sacks of cement by the pump and plug process. Plug down at 9:30 p.m. September 27, 1965. WOC 24 hrs. Temperature Survey indicated cement outside of 4-1/2" OD casing at 3375' from surface. Did not drill out cement plug. FWD 4491.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED (ORIGINAL) H. E. Ash TITLE District Superintendent DATE October 8, 1965

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: