

COUNTY	ROOSEVELT		FIELD	Milnesand-SA		STATE	N.M.	
OPR	SOCONY MOBIL OIL COMPANY, INC.							
	4		Jacobs-Federal		MAP 30-D41-10147			
	Sec. 19,		T-8-S,		R-35-E		CO-ORD	
	1980' fr S & E Lines of Sec.							
	Spud		5-14-64		CLASS		EL 42258	
	Comp		5-30-64					
			FORMATION		DATUM		FORMATION	
			DATUM					
CSG & SX - TUBING			LOG:					
			Rust		2191			
8 5/8" 378' 350			Yates		2685			
4 1/2" 4785' 1375			Queen		3388			
			SA		3896			
			Slaughter					
LOGS EL GR RA IND HC A			4653					
			TD 4785'		PBD 4748'			

IP San Andres Perfs 4653-4725' Pmpd 147 BOPD + 3 BW. Pot.
Based on 24 hr test, gravity 18.4, GOR 595.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Sitton & Norton Drlg. Co.	PROP DEPTH	4800'	TYPE
DATE			

F.R. 5-21-64; Oper's Elev. 4226' KB
PD 4800' - SA
Contr. - Sitton & Norton Drlg. Co.
5-25-64 Drlg. 4769'.
6-1-64 TD 4785', prep to Frac.
Perf (SA) @ 4653', 4655', 4657', 4659', 4670',
4672', 4674', 4675', 4677', 4678', 4698', 4700',
4702', 4705', 4707', 4709', 4719', 4721', 4723' &
4725' W/1 SPI
Ac. 1500 gals.
Swbd 70 BNO, 68 BLO & 31 BAW/23 hrs.
5-8-64 TD 4785', PBD 4748', WO Pumping Unit
Frac 20,000 gals oil + 40,000# sd.
6-15-64 TD 4785', PBD 4748', pmpg load.
Pmpd 120 BLO/22 hrs (-479 BLO)
6-22-64 TD 4785', PBD 4748', COMPLETED.
5-29-64 TD 4785', PBD 4748', Completion Reported.