Form C-103 State of New Mexico xSubmit 3 Copies To Appropriate District Office Revised March 25, 1999 _nergy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-041-10149 District II OIL CONSERVATION DIVISION 81. South First, Artesia, NM 88210 5. Indicate Type of Lease 2040 South Pacheco District III STATE \Box FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 State Oil & Gas Lease No. District IV 2040 South Pacheco, Santa Fe, NM 87505 7. Lease Name or Unit Agreement Name: SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A MILNESAND UNIT DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: **INJECTION** Oil Well Gas Well Other 8. Well No. 26 2. Name of Operator J. CLEO THOMPSON 9. Pool name or Wildcat Address of Operator MILNESAND (SAN ANDRES) 325 N. ST. PAUL. SUITE 4300, DALLAS, TX 75201 Well Location Unit Letter P: 660 feet from the SOUTH line and 660 feet from the EAST line **NMPM** County R00SEVELT Range 35E Township 8S 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4220' GL 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: ALTERING CASING PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ☐ CHANGE PLANS TEMPORARILY ABANDON **ABANDONMENT** CASING TEST AND ☐ MULTIPLE PULL OR ALTER CASING **CEMENT JOB** COMPLETION OTHER: REPAIRED INJECTION WELL OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 1.) RU. POOH W/TBG & OLD PACKER. LEFT OLD PACKER SLIPS IN HOLE. 2.) RIH WITH BIT & SCRAPER & TAGGED BOTTOM @ 4683'. RIH WITH MILL AND 2 7/8 TBG AND CLEANED OUT TO 4768' & TAGGED BOTTOM @ 4683'. 3.) RIH W/2 7/8 X 4 1/2 PERMANENT PACKER WITH BLANKING PLUG AND SET @ 4267'. 4.) RIH W/2 7/8, 6.5#/FT J-55 & N-80 TBG WITH SEAL ASSY AND STINGER ON END. 5.) CIRCULATE 300 SX CLASS C CEMENT BETWEEN 2 7/8 AND 4 ½ CASING & UPON FLUSHING LATCH 2 7/8 TBG IN PACKER. CIRCULATED 105 SX TO PIT. 6.) RIH W/2 1/16" X 2 7/8" INJECTION PACKER ON 2 1/16". PC TBG AND SET PACKER @ 4236'. 7.) CIRCULATE PACKER FLUID, SET PACKER, AND TEST ANNULUS TO 500 PSI, & RETURN WELL TO INJECTION. (4 ½ 9.5#@. 4780', PERFS 4658-4718') I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TITLE

TITLE

ENGINEER

DATE 12/18/00

DATE

164 00

Telephone No. (915)366-8886

SIGNATURE

Type or print name

(This space for State use)

APPPROVED BY

Conditions of approval, if any:

JIM STEVENS