

xSubmit 3 Copies To: Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artes a. NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-041-10149

5. Indicate Type of Lease

STATE ☐ FEE ☒ X

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:
MILNESAND UNIT

8. Well No. 26

9. Pool name or Wildcat
MILNESAND (SAN ANDRES)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ INJECTION

2. Name of Operator

J. CLEO THOMPSON

3. Address of Operator

325 N. ST. PAUL. SUITE 4300, DALLAS, TX 75201

4. Well Location

Unit Letter P 660 feet from the SOUTH line and 660 feet from the EAST line

Section 19 Township 8S Range 35E NMPM County ROOSEVELT

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

4220' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: REPAIR INJECTION WELL ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1.) RU. POOH W/TBG & OLD PACKER. RIH W/BIT & SCRAPER TO BOTTOM & CLEAN OUT.

2.) RIH WITH PACKER AND PLUG TEST CSG. IF CSG NEEDS REPAIR & IF CEMENT SQUEEZING LOOKS DOUBTFUL TO REPAIR LEAK THEN:

3.) RIH W/2 7/8 X 4 1/2 PERMANENT PACKER WITH BLANKING PLUG AND SET @ 4470'.

4.) RIH W/2 7/8, 6.5#/FT J-55 & N-80 TBG WITH SEAL ASSY AND STINGER ON END.

5.) CIRCULATE 250 SX CLASS C CEMENT BETWEEN 2 7/8 AND 4 1/2 CASING & UPON FLUSHING LATCH 2 7/8 TBG IN PACKER.

6.) RIH W/2 1/16" X 2 7/8" INJECTION PACKER ON 2 1/16", PC TBG AND SET PACKER @ 4450'.

7.) CIRCULATE PACKER FLUID, SET PACKER, AND TEST ANNULUS TO 500 PSI. & RETURN WELL TO INJECTION. (4 1/2 9.5#@ 4780'. PERFS 4658-4718')

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

J. E. Stevens

TITLE

ENGINEER

DATE 10/06/00

Type or print name

JIM STEVENS

Telephone No. (915)366-8886

(This space for State use)

APPROVED BY

Conditions of approval, if any:

TITLE BY CHRIS WILSON
ORIGINAL SIGNED BY
DISTRICT I SUPERVISOR

OCT 10 2000
DATE