

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 060978

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Milnesand (SA) Unit

8. FARM OR LEASE NAME

9. WELL NO.

29

10. FIELD AND POOL, OR WILDCAT

Milnesand

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T8S, R35E

12. COUNTY OR PARISH

Roosevelt

13. STATE

NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

UNION TEXAS PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

1400 Wilco Bldg., Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

Unit Letter "N", 660' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4203' GL, 4313' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREAT ☐MULTIPLE COMPLETION ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOT OR ACIDIZE ☐ABANDON* ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☒REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Sept. 27, 1983 - 1. MIRUSU - removed wellhead and installed BOP.
2. Set CIBP on wireline @ 4587' and dumped 35' of Class "C" cement on top.
3. Ran in hole w/2 3/8" tbg. & displaced hole w/10# mud laden gel.
4. Placed 100' cement plug 2200' to 2100'.
5. Placed 100' cement plug 420' to 320'.
6. Removed BOP.
7. Placed 50' plug at surface - cut off csg and welded steel plate across casing.
- Sept. 27, 1983 - 8. Set dry hole marker, cut off anchors and cleaned up location - WELL NOW P&A.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Prod. Services Supr.

DATE 10-5-83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: