

Form approved.
Budget Bureau No. 42-R355.5.

***(See Instructions and Spaces for Additional Data on Reverse Side)**

ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ECT.

Depth Interval	Amount and Kind of Material Used
4647-4657'	1000 gals 15% NE acid + 7 RCN Ball Sealers
4676-4699'	3000 gals 15% NE acid

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions. If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 33.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:

SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Red Bed	0	891	
Red Bed & Salt	891	1606	
Anhy & Salt	1606	2669	
Anhy	2669	3930	
Lime	3930	4800	

38. GEOLOGIC MARKERS

NAME	MEAS. DEPTH	TOP	TRUE VERT. DEPTH
San Andres	3920		
"A" Marker	4636		


DEVIATION TESTS

Socony Mobil Oil Company, Inc.

Jacobs Federal #9,
Unit "N", Sec. 20,
T-8S, "R-35E, Roosevelt
County, New Mexico


<u>Depth</u>	<u>Degree Off Vertical</u>	<u>Depth</u>	<u>Degree Off Vertical</u>
370	1	3,477	3/4
665	3/4	3,740	1
986	3/4	3,940	1 1/4
1,271	3/4	4,127	3/4
1,711	1	4,327	1 1/4
2,025	3/4	4,507	1
2,195	1	4,677	1
2,428	1	4,800	1
2,782	3/4		
3,165	3/4	4,800 TD	

I hereby certify that the above information is true and correct to the best of my knowledge and belief.



Group Supervisor

SUBSCRIBED and Sworn to before me, a Notary Public in and for Lea County, State of New Mexico this 26th day of January, 1965.



Notary Public

My Commission Expires February 19, 1966.