

COUNTY		ROOSEVELT		FIELD		Milnesand-SA		STATE		NM	
OPR		SOCONY MOBIL OIL CO., INC.								MAP	
		9 Jacobs-Federal									
		Sec. 20, T-8-S, R-35-E								CO-ORD	
		660' fr S Line & 1980' fr W Line of Sec.									
		Spud 12-31-64									
		Comp 3-1-65									
		FORMATION		CLASS		EL		FORMATION		DATUM	
CSG & SX - TUBING		LOG:		DATUM							
		SA 3920									
		"A" Marker									
		4636									
LOGS EL GR RA IND HC A											
		TD 4800'		PBD 4771'							

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Rod-Ric Drlg. Co. PROP DEPTH 4800' TYPE

DATE

F.R. 12-31-64
 PD 4800' - SA
 Contractor - Rod-Ric Drlg. Co.
 Drlg. 3554'
 1-4-65 TD 4800', prep to run casing.
 1-11-65 TD 4800', PBD 4771', SI.
 1-18-65 Perf @ 4676', 4678', 4680', 4682', 4684',
 4721', 4723', 4725', 4727', 4743', 4745',
 4749' W/1 SPI
 Ac. 1000 gals.
 Swbd 8 BNO + 14 B Salt Wtr in 6 hrs.
 Re-Perf @ 4676', 4678', 4680', 4682', 4684',
 4721', 4723', 4725', 4727', 4743', 4745',
 4749' W/1 SPI
 Swbd 44 B Salt Wtr in 24 hrs.
 Frac 10,000 gals oil + sand. 4676-4749'.

1-25-65 TD 4800', PBD 4771', pmpg load.
Swbd 35 BLO + 126 B Salt Wtr in 20 hrs
(-213 BLO).

2-1-65 TD 4800', PBD 4771', pmpg load.
Pmpd 31 BLO + 211 B Salt Wtr in 36 hrs.
(-94 BLO).

2-8-65 TD 4800', PBD 4771', pmpg load.
Pmpd 26 BLO + 448 B Salt Wtr in 72 hrs
(-27 BLO).

2-15-65 TD 4800', PBD 4771', WOC.
Pmpd 7 BLO + 1 BNO & 72 B Salt Wtr in 18
hrs.
Squeezed perfs 4676-4749'

2-18-65 TD 4800', PBD 4771', swbg.
Perf @ 4637', 4639', 4641', 4643', 4645',
4653', 4655', 4657' W/1 SPI.

Ac. 1000 gals.
Swbd 3 BLO + 3 BAW/11 hrs.

2-26-65 TD 4800', PBD 4771', SI.
Re-Perf @ 4676', 4678', 4680', 4682', 4684',
4691', 4693', 4695', 4697', 4699' W/1 SPI
Ac. 3000 gals. 4676-4699'.
Swbd 1 BLO + 7 B Salt Wtr in 2 hrs from
perfs 4637-4699'. (-5 BLO).

3-8-65 TD 4800', PBD 4771', COMPLETED.