		N. C.L. Charles P. O. BOX 1980	S STON
Porm 3160-5 (December 1989)	UNITED ST DEPARTMENT OF 7 BUREAU OF LAND	TATES HOBBS, NEW ME.	FORM APPROVED Budget Bureau No. 1004-0135 Expires: September 30, 1990 5 Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS			LC-060978
SI Do not use this form Use	6 If Indian, Allottee or Tribe Name SETVDIT.		
	7. If Unit or CA, Agreement Designation		
1. Type of Well X Oil Gas Well Well Well	MILNESAND (SAR) UNIT 8. Well Name and No.		
2. Name of Operator XERIC OIL & GAS COMPANY			210 9. API Well No.
3. Address and Telephone No.			30-041-10153
P.O. BOX 51311, MIDLAND, TEXAS 79710 (915)683-3171			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Se	MILNESAND (SAN ANDRES		
1720FSL,660F	11. County or Parish, State ROOSEVELL		
CHECK AP	PROPRIATE BOX(S) TO	INDICATE NATURE OF NOTICE	, REPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACT			ACTION
X Notice of Inte	:nt	Ahandonmeni	Charge of Plans
L -1		Recompletion	New Construction
L Subsequent R	eport	Plugging Back	Non-Routine Fracturing
Final Abando	inment Notice	L Casing Repair Altering Casing	Water Shut-Off
		X Other Mechar	ical Integrity Test
		Recomple	port results of multiple completion on Well Completion or tion Report and Log form.) late of starting any proposed work. If well is directionally drilled
for mechanical	integrity to 500	r will be set. Well w Opsi for 30 minutes. test, if desired.	ill be pressure tested BLM will be notified
	. 1		
14. I hereby certify that the forego	oing is true too correct		
Signed	Alfad	THE OPERATIONS MANAGER	Date 10-29-92
(This space for Federal or Sta	ie office yest		
Approved by Conditions of approval, if any	See allacked	Tile Slips	PETER W CHESTER
Title 18 U.S.C. Section 1001 mink	es it a crime for any person knowingly		the United States any fail 92 icus of fraudulent statements
or representations as to any matter	within its jurisdiction		LIREAT TO THE STATE OF THE STAT
		See Instruction on Reverse Side	ROSWELL RESOURCE AREA

RECEIVED

Ν.

NOV 2 0 1992



:

Additional Stipulations for Casing Integrity Test

1. The cast iron bridge plug shall be set within 100 ft. of the upper most perforations or casing shoe if completed open hole.

2. Also notify the New Mexico Oil Conservation Division (NMOCD) prior to test.