NUMBER OF COPIES ECEIVED DISTRIBUTION SANTA F(FILE U.S.G.S. LAND OFFICE TRANSPORTER GAS PHORATION OFFICE		M	MEXICO O	EOUS	REP	ORTS ON	WELLS	∎ 1106)	FORM C103 (Rev 3-55)
OPERATOR				Address			PR 11	- /// ()	04
ame of Company Sun	011 Com					2792, Ode	ssa, Tor	Range	
ease G. N. Cost	y	Wel	1 No. Unit	Letter	12	Township T-8-	3	Kange	R-34-8
te Work Performed	P	Milnesand	(San And	res)		County Roo	sevelt		
			REPORT OF:				• 1 - 1 - 1 -		
Beginning Drillin Plugging	g Operations		g Test and Cen lial Work	nent Job		Content (Exp Acidizing		uring,	Testing
700.1=7009=700				1617	18 at	w/2 3/8"	22-4623	-6064	4027-4020-
4627-4628. Rd On 3-30-63 Ca: at 4645 and p w/2000 gals 1: press 3300#, 5 minute shut	eran tubi rdinal ac acker at 5% MEC ac win treat	4673. Raised id w/42 ball press 2400#	at 4645 al w/500 gal tubing to sealers. final tr	d pack s 15% M o seat BDP w/	at 4	t 4673. aid spotte 582 and pe - tubing 900#, shut	d acros acker at press 2 down pr	s perf 4570. 600, m ess 20	s v/seat Acidized a x treat
4627-4628. Re On 3-30-63 Can at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut	eran tubi rdinal ac acker at 5% MEC ac win treat	ng with seat idised perfs 4673. Raised id w/42 ball press 2400#, 1800#. Swal	at 4645 an w/500 galu tubing to sealers. final tr b testing. Position For	Gal 7-40 nd pack s 15% M o seat BDP w/ sat pro	at 4 acid as 2	t 4673. aid spotte 582 and pe - tubing 900#, shut Company Sun	d acros acker at press 2 down pr Oil Com	s perf 4570. 600, m ess 20	s v/seat Acidized a x treat
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut	eran tubi rdinal ac acker at 5% MEC ac min treat in press	ng with seat idised perfs 4673. Raised id w/42 ball press 2400# 1800#. Swal	at 4645 an w/500 gale tubing to sealers. final tro testing. Position For DW FOR REMN	Cal 7-40 ad pack s 15% M o seat BDP w/ eat pro- eman eman EDIAL W	at 4 or at 4 acid or 2 or 8	t 4673. aid spotte 582 and pe - tubing 900#, shut Company Sun	d acros acker at press 2 down pr Oil Com	s perf 4570. 600, m ess 20	s v/seat Acidized a x treat
4627-4628. Re On 3-30-63 Can at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut	eran tubi rdinal ac acker at 5% MEC ac min treat in press	ng with seat idised perfs 4673. Raised id w/42 ball press 2400#, 1800#. Swal	at 4645 an w/500 galu tubing to sealers. final tr b testing. Position For	Cal 7-40 ad pack s 15% M o seat BDP w/ eat pro- eman eman EDIAL W	at 4 or at 4 acid or 2 or 8	t 4673. aid spotte 582 and pe - tubing 900#, shut Company Sun	d acros acker at press 2 down pr 011 Cou	s perf 4570. 500, m ess 20 mpany	s v/seat Acidized a x treat
4627-4628. Rd On 3-30-63 Ca: at 4645 and pu w/2000 gals 1: press 3300%, 1 5 minute shut Witnessed by H. L	ran tubi rdinal ac acker at 55 MEC ac ain treat in press . Patters	ng with seat idised perfs 4673. Raised id w/42 ball press 2400#, 1800#. Swal	at 4645 an w/500 gale tubing to sealers. final tr b testing. Position For DW FOR REMN ORIGINAL	Cal 7-40 ad pack s 15% M o seat BDP w/ eat pro- eman eman EDIAL W	at 4 acid as 2 ork r	Company Sun Producing	d acros acker at press 2 down pr Oil Com LY	s perf 4570. 500, m ess 20 mpany	s v/seat Acidised a x treat OOH, mpletion Date
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut Vitnessed by H. L	ran tubi rdinal ac acker at 55 MEC ac min treat in press . Patters	ng with seat idised perfs 4673. Raised id w/42 ball press 2400% 1800%. Swal ion FILL IN BELC	at 4645 an w/500 gale tubing to sealers. final tr b testing. Position For DW FOR REMN ORIGINAL	eman EDIAL W WELL D	at 4 acid as 2 ork r	Company Sun Producing	d acros acker at press 2 down pr Oil Com LY	s perf 4570. 500, m ess 20 apany	s v/seat Acidized a x treat 00#, mpletion Date
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 tinessed by H. L D F Elev. Fubing Diameter Perforated Interval(s)	ran tubi rdinal ac acker at 55 MEC ac min treat in press . Patters	ng with seat idised perfs 4673. Raised id w/42 ball press 2400% 1800%. Swal ion FILL IN BELC	at 4645 an w/500 gale tubing to sealers. final tr b testing. Position For DW FOR REMN ORIGINAL	Coll Strin	or at 4 acid ac 4 acid as 2 ork R ATA	Company Sun Producing	d acros acker at press 2 down pr Oil Com LY	s perf 4570. 500, m ess 20 apany	s v/seat Acidised a x treat OOH, mpletion Date
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 tinessed by H. L D F Elev. Fubing Diameter Perforated Interval(s)	ran tubi rdinal ac acker at 55 MEC ac min treat in press . Patters	ng with seat idised perfs 4673. Raised id w/42 ball press 2400% 1800%. Swal ion FILL IN BELC	at 4645 an w/500 gale tubing to sealers. final tr b testing. Position For DW FOR REMN ORIGINAL	Coll 7-440 ad pack s 15% M o seat BDP w/ enam enam EDIAL W WELL D Oil Strin	or at 4. acid acid as 2 ork R ATA	t 4673. aid spotte 582 and pa - tubing 900#, shut Company Sun EPORTS ON Producing Heter	d acros acker at press 2 down pr Oil Com LY	s perf 4570. 500, m ess 20 apany	s v/seat Acidised a x treat OOH, mpletion Date
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 itnessed by H. L D F Elev. Fubing Diameter Perforated Interval(s) Open Hole Interval	ran tubi rdinal ac acker at 55 MEC ac min treat in press . Patters	ng with seat idised perfs 4673. Raised id w/42 ball press 2400% 1800%. Swal ion FILL IN BELC	at 4645 an v/500 gali i tubing to sealers. final tro b testing. Position For OW FOR REMN ORIGINAL PBTD	Content of the sector of the s	ALS AN ACTA ACTA AG Diam AG Diam	t 4673. aid spotte 582 and pa - tubing 900#, shut Company Sun EPORTS ON Producing Heter	d acros acker at press 2 down pr Oil Com LY	s perf 4570. 500, m ess 20 pany Con tring Dept	s v/seat Acidised a x treat OOF, mpletion Date
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 itnessed by H. L D F Elev. Fubing Diameter Perforated Interval(s) Open Hole Interval	ran tubi rdinal ac acker at 5% MEC ac ain treat in press . Patters T D	ng with seat idised perfs 4673. Raised id w/42 ball press 2400 1800 Swal FILL IN BELC Tubing Depth Oil Production	at 4645 an v/500 gali sealers. final tro testing. Position For W FOR REMN ORIGINAL PBTD RESULTS O Gas Prod	Content of the sector of the s	ALS AN ACTA ACTA AG Diam AG Diam	L 4673. aid spotte 582 and pe - tubing 900#, shut Company Sun EPORTS ON Producing neter nation(s) Production	d acros acker at press 2 down pr Oil Com LY Interval Oil St	s perf 4570. 500, m ess 20 pany Con tring Dept	s v/seat Acidised a x treat OOH, mpletion Date th Gas Well Potentia
4627-4628. Re On 3-30-63 Ca: at 4645 and pr w/2000 gals 1 press 3300#, 1 5 minute shut 7 itnessed by H. L D F Elev. Fubing Diameter Perforated Interval(s) Open Hole Interval Test I Before	ran tubi rdinal ac acker at 5% MEC ac ain treat in press . Patters T D	ng with seat idised perfs 4673. Raised id w/42 ball press 2400 1800 Swal FILL IN BELC Tubing Depth Oil Production	at 4645 an v/500 gali sealers. final tro testing. Position For W FOR REMN ORIGINAL PBTD RESULTS O Gas Prod	ADIALY ACTION AND ADDRESS AND	or at 4 acid acid acid acid acid acid acid acid	L 4673. aid spotta 582 and particular 582 and particular 582 and particular 582 and particular 582 and particular 582 and particular Sun Company Sun E PORTS ON Producing Heter Producing Producing Producing	d acros accor at press 2 down pr Oil Cou LY Interval Oil St Cubic fee	s perf 4570. 500, m ess 20 apany Con tring Dept	s v/seat Acidized a x treat OOH, mpletion Date th Gas Well Potentia MCFPD
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 itnessed by H. L D F Elev. Fubing Diameter Perforated Interval(s) Open Hole Interval Test I Before Workover After Workover OIL	ran tubi rdinal ac acker at 55 MEC ac ain treat in press . Patters T D Date of Test	ng with seat idised perfs 4673. Raised id w/42 ball press 2400 1800 Swal FILL IN BELC Tubing Depth Oil Production	at 4645 an v/500 gali i tubing to sealers. final tro b testing. Position For W FOR REMN ORIGINAL P B T D RESULTS Gas Prod MC F	Content of the second s	ORK R ATA ORK R ATA ag Diam	L 4673. aid spotta 582 and particular 582 and particular 582 and particular 582 and particular 582 and particular 582 and particular Sun Company Sun E PORTS ON Producing Heter Producing Producing Producing	d acros accor at press 2 down pr Oil Com LY Interval Oil St Cubic fee	s perf 4570. 500, m ess 20 apany Con tring Dept	s v/seat Acidised a x treat OOH, mpletion Date th Gas Well Potentia
4627-4628. Ro On 3-30-63 Ca: at 4645 and provide the second seco	ran tubi rdinal ac acker at 55 MEC ac ain treat in press . Patters T D Date of Test	ng with seat idised perfs 4673. Raised id w/42 ball press 2400 1800 Swal FILL IN BELC Tubing Depth Oil Production BPD	at 4645 an v/500 gali i tubing to sealers. final tro b testing. Position For W FOR REMN ORIGINAL P B T D RESULTS Gas Prod MC F	ADI/-44 Ad pack BDP w/ eat pre- eman EDIAL W WELL D Oil Strin Produci OF WORH uction PD	ATA ATA ATA ATA ATA ATA ATA ATA	t 4673. aid spotta 582 and pa - tubing 900#, shut Company Sun Producing Producing Producing Production BPD tify that the in	d acros accor at press 2 down pr Oil Com LY Interval Oil St Cubic fee	s perf 4570. 500, m ess 20 apany Con tring Dept	s v/seat Acidized a x treat OOH, mpletion Date th Gas Well Potentia MCFPD
4627-4628. Re On 3-30-63 Ca: at 4645 and pe w/2000 gals 1 press 3300#, 1 5 minute shut 7 itnessed by H. L D F Elev. Fubing Diameter Perforated Interval(s) Open Hole Interval Test I Before Workover After Workover OIL	ran tubi rdinal ac acker at 55 MEC ac ain treat in press . Patters T D Date of Test	ng with seat idised perfs 4673. Raised id w/42 ball press 2400 1800 Swal FILL IN BELC Tubing Depth Oil Production BPD	at 4645 an v/500 gali i tubing to sealers. final tro b testing. Position For W FOR REMN ORIGINAL P B T D RESULTS Gas Prod MC F	Content of the second s	ATA Ag Diam ag Diam ag Diam Nag Form COVER Water ebest of ion Ag	t 4673. aid spotta 582 and pa - tubing 900#, shut Company Sun Producing Producing Producing Production BPD tify that the in	d acros accors accors press 2 down pr Oil Cou LY Interval Oil St Cubic fee formation g	s perf 4570. 500, m ess 20 apany Con tring Dept	s v/seat Acidised a x treat OOF, mpletion Date th Gas Well Potenti MCFPD