

COUNTY		Roosevelt		FIELD		Milnesand-San Andres		STATE		N.M.		NO.	
OPR		Sunray DX Oil Company										MAP	
NO.		18 LSE New Mexico-Federal "F"											
SEC.		21		T. 8S		BLK. R		34E		SUR.		CO-ORD.	
LOC.		1980' fr S Line & 660' fr W Line of Sec.											
MI.		FROM		CLASS.		EL.		42945					
SPUD.		7-10-63		COMP.		8-28-63		FORMATION		DATUM		FORMATION	
TRT.		2000 Ac., SOF 20,000		LOG:									
		+ 20,000# sd.		Rust.		2136							
CSG. & SX.				Yates		2606							
		8 5/8" 331' 250		Queen		3300							
		4 1/2" 4649' 200		SA Porosity		4526							
TBG.		DEPTH		SIZE									
LOGS		EL GR RA IND HC A		TD		4650'		PB					
PROD INT.		(DAILY RATE)		BS&W		GH		GOR		GTY		C. P.	
4536-4601'		Ppd. 8 BO + 3		bbls		900		26.5		24'			
(San Andres)		Salt Wtr											
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.													
CONT.		Cactus Drlg. Co.		PROP DEPTH		4600'		TYPE					
DATE													

F.R. 7-5-63, San Andres.

PD 4600' RT - Cactus Drlg. Co., Contractor

7-15-63 Drlg. 4104' dolo.

7-22-63 TD 4650', rec'g load.

Perf 4/4536-38', 6/4554-57', 4/4567-69', 4/4592-94',
& 6/4598-4601', treated 2000 gals acid,
SOF 20,000 gals ref. oil + 20,000# sd.

7-29-63 TD 4650', ppg. load.

Ppd. 22 BLO in 12 hrs (-366).

8-5-63 TD 4650', ppg. load.

Ppd. 28 BLO in 24 hrs (-216).

8-12-63 TD 4650', ppg. load. Ppd. 31 BLO/72' (-147).

8-19-63 TD 4650', ppg. load. Ppd. 26 BLO/48' (-72).

8-26-63 TD 4650', ppg. load. Ppd. 11 BLO/24' (-15).

9-3-63 TD 4650', COMPLETED.

