

COUNTY	ROOSEVELT FIELD Milnesand-SA			STATE	NM
OPR	SUNRAY DX OIL COMPANY			MAP	
	20 New Mexico-Federal "F"				
	Sec. 25, T-8-S, R-34-E			CO-ORD	
	990' fr S Line & 330' fr E Line of Sec.				
	Spud 11-17-64			CLASS	EL 4228
	Comp 12-31-64			FORMATION	DATUM
CSG & SX - TUBING				FORMATION	DATUM
	LOG:				
	Anhy 2173				
	Yates 2690				
	Queen 3402				
	SA 3914				
LOGS EL GR RA IND HC A					
	TD 4902', PBD 4720'				

IP San Andres Perfs 4662-84' Pmpd 16 BOPD + 24 BW. Pot. Based on 24 hr test, gravity 29.4, GOR 1580.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus Drlg. Co. PROP DEPTH 4900' TYPE
DATE

2

F.R. 11-5-64
PD 4900' - SA
Contractor - Cactus Drlg. Co.

11-16-64 MIRT
11-23-64 Drlg. 4130'.
11-30-64 TD 4902', prep to run casing.
12-7-64 TD 4902', PBD 4720', swbg load.
Perf 4728-35' W/2 SPF
Ac. 750 gals.
Swbd 6 BNO + 17 B Salt Wtr in 11 hrs.
Set BP @ 4720'
Perf 4662-69', 4676-78', 4680-84' W/2 SPF
Ac. 1000 gals.
Swbd 2.5 BFPH
Frac 20,000 gals oil + 20,000# sd.

12-14-64 TD 4902', PBD 4720', tstg on pump.
Swbd 160 BLO + 16 BW in 24 hrs.

ROOSEVELT COUNTY Milnesand-SA NM Sec. 25-8S-34E
SUNRAY DX OIL CO., #20 New Mexico-Federal "F"-Page #2

12-21-64 TD 4902', PBD 4720', pmpg load.
Pmpd 23 BLO + 19 BW in 24 hrs (159 BLO).
1-4-65 TD 4902', PBD 4720', COMPLETED.