

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

AUG 25 1 14 PM '65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 3935	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Sunray DX Oil Company		8. Farm or Lease Name N. M. State "AZ"
3. Address of Operator P. O. Box 1416 Roswell, New Mexico		9. Well No. 8
4. Location of Well UNIT LETTER <u>E</u> , <u>1980</u> FEET FROM THE <u>N</u> LINE AND <u>660</u> FEET FROM THE <u>W</u> LINE, SECTION <u>34</u> TOWNSHIP <u>7S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Chaveroo S. A.
15. Elevation (Show whether DF, RT, GR, etc.) Furnish Later		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Spud 11" hole at 6:00 PM, 8-21-65. Drlg to TD 375'.
2. Ran 8 5/8", 24#, J-55 csg to csg point 368'.
3. Cement w/250 sx reg cement 2% CaCl<sub>2</sub>. Cement circ to surface. WOC 18 hours. Tested to 1000 psig for 30 min.--O.K. Now drlg ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John Hastings John Hastings

TITLE Production Engineer

DATE 8-24-65

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: