

COUNTY ROOSEVELT FIELD Wildcat STATE N.M.

WC OPR WOOD, ROBERT L. ET AL MAP

1 Cone-Federal

Sec. 33, T-8-S, R-34-E

1980' fr N Line & 660' fr W Line of Sec.

Spud 1-6-64

Temp. Abd. 2-22-64

		CLASS		EL	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
		Yates 2646			
		SA 3870			
		Slaughter			
		4596			
LOGS EL GR RA IND HC A					
		TD 4750', PB 4644'			

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Basin Drlg. Co. PROP DEPTH 4800' TYPE

DATE

F. R. 1-2-64.
PD 4800' - San Andres., Oper's Elev. 4289'. DF
Contractor - Basin Drlg. Co.

1-13-64 Drlg. 4320' 1m.

1-20-64 TD 4750', prep to DST.
Cored 4555-4605', rec. 48.6' being:
41' anhy & dolo w/NS, 2.5' dolo w/bldg. oil.
2.5' dolo w/ NS, 2.6' dolo w/bldg. oil.

1-27-64 TD 4750', prep to PB.
Attempted DST 4582-4672', pkr. failed.
Attempted DST 4600-4684', pkr. failed.
SP DST 4592-4676', open 5 mins., pkr. failed.
Rec. 1070' Drlg. M + 300' SOCM.
FP 810-851#.
Perf. 4711', 4715', w/1 SPI, Ac. 500 gals.
Swb. 25 BL & AW/2 hrs. & swbd. dry.

2-3-64 TD 4750', PB 4680'.
Perf. 4686-96', & 4708' w/1 SPF, Swb. wtr. w/SSO.
Ac. 500 gals., Frac. 5000 gals. Ac. & 15,000 gals.
wtr. Swb. 1 BO + 102 BLW + 32 BFW/8 hrs. 30 mins.
Sq. perfs. 4686-4715' w/50 sxs.

2-10-64 TD 4750', PB 4680', swbg.
Perf @ 4653', 4655', 4658', 4663', 4666' &
4669' W/1 SPI
Swbd dry.
Ac. 1000 gals (4653-69')
Swbd load & swbd 2 BNO + 27 BFW/6 hrs.
2-17-64 TD 4750', PB 4644', swbg.
Swbd 25 BW, w/tr. oil in 4 hrs (4653-69')
Squeezed perfs 4653-69' W/50 sx.
Set BP @ 4644'
Perf @ 4613', 4620', 4625', 4628', 4631' &
4635' W/1 SPI
Ac. 750 gals.
Swbd 5½ BW/1 hr, with very slight show oil
Swbd 2-3/4 BW/5 hrs.

Ac 5000 gals acid, 10,000 gals wtr & 15,000#
sd.
Swbd 116 BLW/11 hrs.
2-24-64 TD 4750', PB 4644', TEMPORARILY ABANDONED.
Swbd 66 BLW + 17 BFW/11 hrs.