


AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Franklin, Aston & Fair, Inc. American Trading State  
(Company or Operator) (Lease)

Well No. 1, in NW 1/4 of NW 1/4, of Sec 6, T 8 South, R 36 East, NMPM.  
Wildcat Pool, Roosevelt County.  
Well is 660 feet from North line and 660 feet from West line  
of Section 6. If State Land the Oil and Gas Lease No. is E-9680  
Drilling Commenced August 30, 1964. Drilling was Completed September 18, 1964  
Name of Drilling Contractor Monarch Drilling  
Address Hobbs, New Mexico 4161 KB  
Elevation above sea level at Top of Tubing Head 4149 GR. The information given is to be kept confidential until  
19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"		New	275	Set with	150 sax reg neat circulate surface		
4 1/2"	9.5	New	4495	Halliburton	1600'		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8"	263	150	Circulated		
7 13/16"	4 1/2"	4495	200	Circulated	Top cement 3675 ft.	

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforated 1 shot 4460', 4465', 4469', 4473', 4484', 4489', 4494', acidized 1500 gal acid swabbed 3 barrels salt water per hour, some dead oil.  
Perforated 4445', 4473', 4409', 4399', 4349', 4311', 4269', 4256', 4245' acidized with 1500 gallons acid, swabbed salt water slight amount gas, shut in pressure built to  
Result of Production Stimulation 1000 PSI in 36 hours.  
Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from surface feet to 4539' TD feet, and from feet to feet.  
 Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing P & A October 6, 1964

OIL WELL: The production during the first 24 hours was DTA barrels of liquid of which % was  
 was oil; % was emulsion; % water; and % was sediment. A.P.I.  
 Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
 liquid Hydrocarbon. Shut in Pressure lbs.  
 Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):  
 Southeastern New Mexico Northwestern New Mexico

T. Anhy. 2085	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers 2560	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres 3595	T. Granite	T. Dakota
T. Glorieta TD 4539	T.	T. Morrison
T. Drinkard	T.	T. Penn.
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
2085	2560		Anhydrite				
2560	3595		Seven Rivers (?)				
3595	4539		San Andres				
	TD						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Franklin, Aston & Fair, Inc. Address P. O. Box 1090, Roswell, New Mexico  
 Name Grant M. Smith Position or Title Geologist  
 October 8, 1964 (Date)