

COUNTY <u>Roosevelt</u> FIELD <u>Milnesand-San Andres</u> STATE <u>N.M.</u> NO.																																																																																																																																														
OPR <u>Maxwell Oil Company</u> MAP																																																																																																																																														
NO. <u>1</u> LSE <u>Fraser</u> BLK. <u>35E</u> SUR. CO-ORD.																																																																																																																																														
SEC. <u>6</u> T. <u>8S</u> R. <u>35E</u> SUR.																																																																																																																																														
LOC. <u>660' fr S & W Lines of Sec.</u> EL. <u>4265'</u>																																																																																																																																														
<table border="1"> <thead> <tr> <th>MI.</th> <th>FROM</th> <th>FORMATION</th> <th>DATUM</th> <th>FORMATION</th> <th>DATUM</th> </tr> </thead> <tbody> <tr> <td>SPUD.</td> <td>5-2-63</td> <td>COMP. 7-22-63</td> <td></td> <td></td> <td></td> </tr> <tr> <td>TRT.</td> <td>2000 Ac.,</td> <td>SOF 41,000</td> <td>Sample:</td> <td></td> <td></td> </tr> <tr> <td></td> <td>+ 31,000# sd.</td> <td></td> <td>SA</td> <td>3830</td> <td></td> </tr> <tr> <td>CSG. & SX.</td> <td></td> <td></td> <td>LOG:</td> <td></td> <td></td> </tr> <tr> <td></td> <td>8 5/8"</td> <td>368' 250</td> <td>Yates</td> <td>2635</td> <td></td> </tr> <tr> <td></td> <td>4 1/2"</td> <td>4693' 500</td> <td>Queen</td> <td>3333</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>SA</td> <td>3823</td> <td></td> </tr> <tr> <td>TBG.</td> <td>DEPTH</td> <td>SIZE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>LOGS</td> <td>EL</td> <td>GR RA</td> <td>IND HC A</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>TD 4700'</td> <td>PB 4660'</td> </tr> <tr> <td colspan="10"> <table border="1"> <thead> <tr> <th>PROD INT.</th> <th>(DAILY RATE)</th> <th>BS&W</th> <th>GH</th> <th>GOR</th> <th>GTY</th> <th>C. P.</th> <th>T. P.</th> <th>HRS. TEST</th> </tr> </thead> <tbody> <tr> <td>4551-4634'</td> <td>Pump 42 BO + 2 BW</td> <td></td> <td></td> <td></td> <td>30.</td> <td></td> <td></td> <td>24'</td> </tr> <tr> <td colspan="9">(San Andres)</td> </tr> </tbody> </table> </td> </tr> <tr> <td colspan="10"> Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc. </td> </tr> <tr> <td colspan="10"> CONT. <u>Monarch Drlg. Co.</u> PROP DEPTH <u>4750'</u> TYPE </td> </tr> <tr> <td colspan="10">DATE</td> </tr> </tbody></table>										MI.	FROM	FORMATION	DATUM	FORMATION	DATUM	SPUD.	5-2-63	COMP. 7-22-63				TRT.	2000 Ac.,	SOF 41,000	Sample:				+ 31,000# sd.		SA	3830		CSG. & SX.			LOG:				8 5/8"	368' 250	Yates	2635			4 1/2"	4693' 500	Queen	3333					SA	3823		TBG.	DEPTH	SIZE				LOGS	EL	GR RA	IND HC A							TD 4700'	PB 4660'	<table border="1"> <thead> <tr> <th>PROD INT.</th> <th>(DAILY RATE)</th> <th>BS&W</th> <th>GH</th> <th>GOR</th> <th>GTY</th> <th>C. P.</th> <th>T. P.</th> <th>HRS. TEST</th> </tr> </thead> <tbody> <tr> <td>4551-4634'</td> <td>Pump 42 BO + 2 BW</td> <td></td> <td></td> <td></td> <td>30.</td> <td></td> <td></td> <td>24'</td> </tr> <tr> <td colspan="9">(San Andres)</td> </tr> </tbody> </table>										PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST	4551-4634'	Pump 42 BO + 2 BW				30.			24'	(San Andres)									Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.										CONT. <u>Monarch Drlg. Co.</u> PROP DEPTH <u>4750'</u> TYPE										DATE									
MI.	FROM	FORMATION	DATUM	FORMATION	DATUM																																																																																																																																									
SPUD.	5-2-63	COMP. 7-22-63																																																																																																																																												
TRT.	2000 Ac.,	SOF 41,000	Sample:																																																																																																																																											
	+ 31,000# sd.		SA	3830																																																																																																																																										
CSG. & SX.			LOG:																																																																																																																																											
	8 5/8"	368' 250	Yates	2635																																																																																																																																										
	4 1/2"	4693' 500	Queen	3333																																																																																																																																										
			SA	3823																																																																																																																																										
TBG.	DEPTH	SIZE																																																																																																																																												
LOGS	EL	GR RA	IND HC A																																																																																																																																											
				TD 4700'	PB 4660'																																																																																																																																									
<table border="1"> <thead> <tr> <th>PROD INT.</th> <th>(DAILY RATE)</th> <th>BS&W</th> <th>GH</th> <th>GOR</th> <th>GTY</th> <th>C. P.</th> <th>T. P.</th> <th>HRS. TEST</th> </tr> </thead> <tbody> <tr> <td>4551-4634'</td> <td>Pump 42 BO + 2 BW</td> <td></td> <td></td> <td></td> <td>30.</td> <td></td> <td></td> <td>24'</td> </tr> <tr> <td colspan="9">(San Andres)</td> </tr> </tbody> </table>										PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST	4551-4634'	Pump 42 BO + 2 BW				30.			24'	(San Andres)																																																																																																																		
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST																																																																																																																																						
4551-4634'	Pump 42 BO + 2 BW				30.			24'																																																																																																																																						
(San Andres)																																																																																																																																														
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.																																																																																																																																														
CONT. <u>Monarch Drlg. Co.</u> PROP DEPTH <u>4750'</u> TYPE																																																																																																																																														
DATE																																																																																																																																														

F.R. 5-2-63, San Andres
 Contractor - Monarch Drlg. Co., PD 4750'.
 Drlg. 3671'.
 5-7-63 Coring below 4659'.
 5-13-63 Cored 4555-4607', rec 52' being: 38' dense dolo.,
 w/some bldg., 14' dolo., BO&G from fracs & PPP.
 Cored 4607-4659', rec 52' being: 38' dolo., w/
 scatt. bldg. from hairline fracs & PPP, 14' dense
 tight dolo.
 5-20-63 TD 4700', PB 4660', WO Pump.
 Cored 4659-4688', rec 29' dense dolo., w/NS
 Perf 1 shot @ 4551', 4559', 4570', 4596', 4606',
 4615', 4625', & 4634', treated 2000 gals acid.
 Swbd 40 BLO + 44 BNO & 6 BAW + 50 BNW in 14 hrs.
 Swbd 14.5 BFPH for 14 hrs (70-80% wtr).
 5-27-63 TD 4700', RU Pump.
 6-3-63 TD 4700', tstg. PPD. 24 BO + 246 BW/24 hrs.

Maxwell Oil Company, #1 Whaley - Sec. 6-8S-35E

6-10-63 TD 4700', prep to frac.
Ppd. 24 BO + 261 BW in 24 hrs & squeezed perfs
4551-4634' with 238 sx.
Re-Perf 1 shot @ 4551', 4559', 4570', 4575',
4606', 4615', 4625', & 4634', treated 2000 Ac.
Swbd dry, with slight show of oil.
6-17-63 TD 4700', swbg load.
SOF 11,000 gals + 11,000# sd.
Fld. 170 BLO & died.
Re-SF with 30,000 gals + 20,000# sd.
6-24-63 TD 4700', PB 4660', PPG. load.
7-1-63 TD 4700', PB 4660', PPG. load, no gauge.
7-8-63 TD 4700', PB 4660', PPG. load. Ppd. 7 BLOPD.
7-15-63 TD 4700', PB 4660', PPG. load.
7-22-63 TD 4700', PB 4660', PPG. load. (-230 BLO).
Ppd. 4 BLOPD.

7-29-63 TD 4700', PB 4660', PPG. load.
8-5-63 TD 4700', PB 4660', PPG. load.
8-6-63 TD 4700', PB 4660', COMPLETED.
(Holding for amended lease designation).
8-8-63 AMENDED Lease Designation: was Whaley.
8-12-63 TD 4700', PB 4660', Completion Reported.