

APPROVED

(SUBMIT IN TRIPLICATE)

Land Office

61334 M
FM 0134-B

Lease No.

N

Unit

OCT 21 1963

UNITED STATES

DEPARTMENT OF THE INTERIOR

J. L. GORDON

GEOLOGICAL SURVEY

ACTING DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Tesaco Federal

October 18

63

Well No. 1 is located 660' ft. from N line and 660' ft. from E line of sec. 7

SW/4 SW/4

7-5

35-2

NMPM

Wilcox (Field)

Roosevelt (County or Subdivision)

(Meridian)

New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4215 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 4315' of used J-55, 11.6 lb., 8-rd. 4 1/2" casing with a float collar at 4300' and guide shoe at 4315'. Cemented with 120 ax of regular. Held 500lb. pressure on casing for 42 hrs.. Pressure held. PSTD 4298' from ground level. Ran temperature survey and found top of cement at 3400'. B J Service performed the work.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Jack L. McClellan

Company

Box 348

Address

Roswell, New Mexico

By

Operator

Title