

COOR. ROOSEVELL FIELD Milnesand-SA		STATE N.M.	
OPR PAN AMERICAN PETROLEUM CORPORATION		MAP	
8 Horton, Russell E.-Federal			
Sec. 30, T-8-S, R-35-E		CO-ORD	
2310' fr S Line & 1650' fr W Line of Sec.			
Spud 6-30-64		CLASS	
Comp. 7-23-64		Elev. 4225'	
		FORMATION	DATUM
		FORMATION	DATUM
LOGS		LOG:	
5/8" 409' 250		SA 3906	
4 1/2" 4700' 200			
LOGS EL GR RA IND HC A		TD 4700', PBD 4698'	

TP San Andres Perfs. 4656-93', Flowed 160 BOPD + 15 BW. Pot.
Based on 24 hr. test thru 20/64" chk., TP 100#, CP 150#, Gty.
30., GOR 512.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Consulting Service, Inc.

CONT. Cactus Drlg. Co.	PROP DEPTH 4700'	TYPE
DATE		

F. R. 7-9-64; Oper's Elev. 4225' DF.
PD 4700' - San Andres.
Contractor - Cactus Drlg. Co.
7-3-64 Drlg. 2730'.
7-13-64 TD 4700', PB 4698', prep to frac.
Perf. 4656-64', 4670-78', 4680-93' w/2
SPF.
7-20-64 TD 4700', PB 4698', tstg. on pump.
Frac. 20,000 gals. oil + 24,000# sd.
Flow 110 BLO/24 hrs. thru 24/64" chk.,
Ppd. 65 BLO + 20 BW/33 hrs.
7-27-64 TD 4700', PBD 4698', COMPLETED.
Ppd. 119 BLO + 31 BNO & 20 BW/24 hrs.