

COUNTY	ROOSEVELT		FIELD	Todd		STATE	NM	
OPR	FRANKLIN, ASTON & PAIR, INC.						MAP	
	5 Mark-Federal							
	Sec. 25, T-7-S, R-35-E						CO-ORD	
	330' fr S Line & 1650' fr E Line of Sec.							
	Spd 8-23-65						CLASS	
	Cmp 10-21-65						E	
	FORMATION		DATUM		FORMATION		DATUM	
CSG & SX - TUBING								
8 5/8"		275'		250				
5 1/2"		4315'		300				
LOGS EL GR RA IND HC A								
TD 4315'								

IP San Andres Perfs 4213-47' Pmpd 30 ECPD + 8 BW. Pot. Based on 24 hr test.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Verna Drlg. Co.	PROP DEPTH	4400'	TYPE
DATE				

F.R. 8-19-65
PD 4400' - SA
Contractor - Verna Drlg. Co.

8-30-65 Drlg. 4072'
9-7-65 TD 4315', tstg.
Cored 4210-64', rec 50' dolo., w/scatt PP to
Vuggy Porosity, bleeding oil.
Perf @ 4213', 4215', 4223', 4225', 4227',
4232', 4236', 4238', 4242', 4245', 4247'
W/I SPI
Ac. 4250 gals.
Swbd slight show oil & gas.

9-13-65 TD 4315', installing pumping equipment.
Frac 20,000 gals oil + 20,000# sd. 4213-47'.
9-20-65 TD 4315', pmpg load.
9-27-65 TD 4315', pmpg load.
10-4-65 TD 4315', pmpg load.

ROCSEVELT Eccc NM Sec. 25-7S-35E
FRANKLIN, ASTON & FAIR, INC., #5 Mark-Federal Page #2

09-11-65 TD 4315', pmpg load.
10-18-65 TD 4315', pmpg load.
10-25-65 TD 4315', pmpg load.
11-1-65 TD 4315', COMPLETED.
LOG TOPS: San Andres 3468', Slaughter
4100'.