

COUNTY <u>ROOSEVELT</u>		FIELD <u>Chaveroo</u>		STATE <u>NM</u>	
OPR <u>CHAMPLIN PETROLEUM CO.</u>			MAP		
<u>4 Lauck-Federal</u>					
Sec. <u>29, T-7-S, R-33-E</u>			CO-ORD		
<u>660' FSL & 1980' FEL of Sec.</u>					
Spd <u>10-26-65</u>			CLASS		
Cmp <u>11-16-65</u>		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 365' 200					
4 1/2" 4453' 325					
LOGS EL GR RA IND HC A					
TD 4454', PBD 4448'					

IP San Andres Perfs 4288-4406' Swbd 165 BOPD + 15 BW. Pot. Based on 24 hr test, gravity 24.6, GOR 600.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. <u>Sitten & Norton</u>	PROP DEPTH <u>4500'</u>	TYPE
DATE		

- F.R. 10-28-65
- PD 4500' - SA
- 11-1-65 Drlg. 3875'.
- 11-8-65 TD 4454', WOC.
DST 4188-4454', open 1 hr 30 mins,
rec 125' sli GCM,
1 hr ISIP 1194#, FP 229-258#,
1 hr 30 min FSIP 968#.
- 11-15-65 TD 4454', PBD 4448', swbg load.
Perf @ 4288', 4308', 4318', 4331', 4332',
4351', 4398', 4406' W/1 SPI
Ac. 2500 gals.,
Frac 40,000 gals wtr + 40,000# sd.
Swbd 230 BF (15% oil) in 24 hrs.
- 11-22-65 TD 4454', PBD 4448', COMPLETE.
LOG TOPS: Yates 2315', Queen 2988', San
Andres 3546'.

