

Form 9-331
(May 1963)

HOBBS OFFICE O. C. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM0108997(A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL X 1980' FWL, Sec. 28, (Unit K, NW/4 SW/4)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. F. FARRELL-USA

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

CHAUEROO SAN ANDRES

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-7-33 NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4432' R. D. B.

12. COUNTY OR PARISH

ROOSEVELT

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4454. On 11-26-65, 4 1/2" OD 9.5" J-55 casing was set at 4454' w/500 sq 12% Gel + 300 sq. Incon. near. TCMT-2550. Tested casing w/1500 psi for 30 minutes. Test O.K. Perforated intervals 4248-50; 4260-62; 4270-72; 4276-79; 4287-89; 4296-98; 4310-12; 4337-39; 4398-4402 w/2JSPF. Acidized w/200 gallons and Graced w/30,000 gal oil & 45,000 # sand. Swabbed in and evaluated.

On PT. pumped 129 BO x OBW in 24 hours.
Cgr 35°. GOR NA,

TD 4454 PBD 4418 TPA 4248 San Andres

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Foreman

DATE

12-9-65

(This space for Federal or State office use)

04- USGS

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY.

TITLE

APPROVED

DATE

DEC 13 1965

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER

1-JGB
1-SJS
1-RP
2-Champin
1-Warren Am
1-Kern Co hand
3-Tom Ahearn