

COUNTY	ROOSEVELT			FIELD	Undesignated	STATE	NM
OPR	SMITH, W. G. JR.			MAP			
1 Atlantic-State							
Sec. 32, T-7-S, R-35-E				CO-ORD			
1980' fr N & E Lines of Sec.							
Spd 4-15-65				CLASS			
Cmp 12-2-65				E			
		FORMATION	DATUM			FORMATION	DATUM
CSG & SX - TUBING							
8 5/8" 247' 175							
4 1/2" 4556' 250							
LOGS EL GR RA IND HC A							
		TD 4559'					

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Monarch
DATE
PROP DEPTH 4500' TYPE

F.R. 4-22-65
FD 4500' - SA
Contractor - Monarch

4-26-65 TD 36', SDR.
4-27-65 Drlg. 93'.
5-3-65 TD 247', WOC.
5-10-65 Drlg. 3450'.
5-17-65 Drlg. 4257'.
5-24-65 TD 4559', WOC.
Cored 4493-4544', rec 51' dolo., w/scatt
good show oil & some wtr.
6-1-65 TD 4559', PBD 4556', swbg.
Perf @ 4491', 4500', 4508', 4537' W/4 SPI
Ac. 4000 gals.
6-7-65 TD 4559', PBD 4556', SI.
Swbd dry.

6-14-65 TD 4559', PBD 4556', swbg.
Re-Perf @ 4491', 4500', 4508', 4537' W/2
SPI
Set Pkr @ 4533'
Ac. 1000 gals.
Swbd acid wtr, w/show oil & gas.
6-21-65 TD 4559', PBD 4520', SI.
Squeezed perfs 4491-4537'
Drld out to 4520'
Re-Perf @ 4491', 4497', 4508' W/2 SPI
Ac. 500 gals.
Swbd down, w/slt show oil.
6-28-65 TD 4559', PBD 4520', prep to squeeze.

7-6-65 TD 4559', PBD 4520', pmpg load
Squeezed perfs 4491-4508' W/100 sx.
Sand Jet @ 4538'
Frac 600 BW + 12,000# sd. 4538'.
Flwd 175 BLW, w/show oil.
Sand Jet @ 4491'
Frac 600 BW + 16,000# sd. 4491'
7-12-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.
7-19-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr, w/RB show oil.
7-26-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.
8-2-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 63 B Salt Wtr/24 hrs.
8-9-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr, w/RB show oil.

8-16-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

8-23-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

8-30-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

9-7-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

9-13-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

9-20-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

9-27-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

10-4-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

10-11-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

10-18-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

10-25-65 TD 4559', PBD 4520', tstg on pump.
Pmpd 100% salt wtr.

11-1-65 TD 4559', PBD 4480', tstg.
Perf @ 4380', 4388', 4399', 4418',
4428', 4435', 4466' W/1 SPI
Set BP @ 4480'
Ac. 1250 gals. 4380-4466'

11-8-65 TD 4559', PBD 4480', tstg.
No Gas Gauge.

11-15-65 TD 4559', PBD 4480', tstg., no gauge.

ROOSEVELT Undesignated NM
SMITH, W. G. JR., #1 Atlantic-State

Sec. 32-7S-35E
Page #4

11-22-65 TD 4559', PBD 4480', tstg., no gauge.
11-29-65 TD 4559', PBD 4480', Prep to P&A.
12-6-65 TD 4559', PBD 4480', PLUGGED & ABANDONED.
LOG TOPS: San Andres 3680',
Slaughter 4243'.