

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Form C-105
Revised 1-1-65

HUBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOG
DEC 28 11 58 AM '65

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. E - 1369

1a. TYPE OF WELL OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Unit Agreement Name -
b. TYPE OF COMPLETION NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐	8. Farm or Lease Name Hobbs "T" T.B. # 2
2. Name of Operator Shelly Oil Company	9. Well No. 12
3. Address of Operator Box 730 - Hobbs, New Mexico	10. Field and Pool, or Wildcat Cherokee San Andres

4. Location of Well UNIT LETTER "T" LOCATED 1900 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE OF SEC. 34 TWP. 7-S RGE. 33-E NMMPM	12. County Hessavalt
---	--------------------------------

15. Date Spudded 11-28-65	16. Date T.D. Reached 11-30-65	17. Date Compl. (Ready to Prod.) 12-11-65	18. Elevations (DF, RKB, RT, GR, etc.) 4304'	19. Elev. Casinghead -
20. Total Depth 4475'	21. Plug Back T.D. 4441'	22. If Multiple Compl., How Many -	23. Intervals Drilled By Rotary Tools 0-4475	Cable Tools -
24. Producing Interval(s), of this completion - Top, Bottom, Name 4321 - 4353' -(Intervals) - San Andres				25. Was Directional Survey Made NO

26. Type Electric and Other Logs Run Schlumberger: Sidewall Gamma Ray Neutron, Compensated Formation Density Log, Laterolog, Microlaterolog, Sonic Log; Nelson: Gamma Ray Neutron Collar Log	27. Was Well Cored NO
--	---------------------------------

28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8	24	370'	11"	230	-
4-1/2	10.5	4475'	7-7/8"	320	-

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
None					2-3/8	4216'	

31. Perforation Record (Interval, size and number) See Attached Sheet	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. <table border="1"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>4380-4393'</td> <td>1000 gal. reg. NE Acid</td> </tr> <tr> <td>4321-4353'</td> <td>2000 gal. Spontaneous Acid</td> </tr> <tr> <td>4321-4353'</td> <td>10000 gal. loose oil & 40000 lbs. 20-40</td> </tr> </table>	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	4380-4393'	1000 gal. reg. NE Acid	4321-4353'	2000 gal. Spontaneous Acid	4321-4353'	10000 gal. loose oil & 40000 lbs. 20-40
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED								
4380-4393'	1000 gal. reg. NE Acid								
4321-4353'	2000 gal. Spontaneous Acid								
4321-4353'	10000 gal. loose oil & 40000 lbs. 20-40								

33. PRODUCTION							
Date First Production 12-11-65		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing				Well Status (Prod. or Shut-in) Producing	
Date of Test 12-12-65	Hours Tested 24	Choke Size 32/64	Prod'n. For Test Period →	Oil - Bbl. 432	Gas - MCF 255	Water - Bbl. 8	Gas - Oil Ratio 590
Flow Tubing Press. 100 psi	Casing Pressure 900 psi	Calculated 24-Hour Rate →	Oil - Bbl. 432	Gas - MCF 255	Water - Bbl. 8	Oil Gravity - API (Corr.) 21.6°	

34. Disposition of Gas (Sold, used for fuel, vented, etc.) Vented	Test Witnessed By B. L. Holley
---	--

35. List of Attachments Item # 31 (Perforation Record)
--

36. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.		
SIGNED (ORIGINAL SIGNED) H. E. A.	TITLE District Superintendent	DATE December 27, 1965

HOBBS OFFICE O. C. C.
DEC 28 11 58 AM '65

Wells "T" T.B. # 2 Well No. 12

Item 31. Perforation Record

Perforation Job No. 1 4320 - 4353'

Perforated 4-1/2" OD casing with 1 Jet shot per foot at the following depths: 4320', 4325', 4329', 4339', 4345', 4350.5', 4353', a total of 7' & 7 shots.

Perforation Job No. 2 4321 - 4311'

Perforated 4-1/2" OD casing with 1 Jet shot per foot at the following depths: 4321', 4321', 4326', 4340', 4372.5', 4379', 4384', 4387', 4397', 4305.5', 4309', 4311', a total of 12' and 12 shots.