

COUNTY	ROOSEVELT			FIELD	Chaveroo		STATE	NM	
OPR	PAN AMERICAN PETROLEUM CORP.							MAP	
	1 State "DA"								
	Sec. 35, T-7-S, R-33-E							CO-ORD	
	1980' ENL, 660' FWL of Sec.								
	Spd 1-12-66			CLASS	EL [REDACTED]				
	Cmp 2-20-66			FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING									
8 5/8"	432'	250							
4 1/2"	4466'	800							
LOGS	EL	GR	RA	IND	HC	A			
				TD 4466', PBD 4437'					

IP San Andres Perfs 4205-4332' Pmpd 47 BOPD + 3 BW. Pot.
Eased on 24 hr test, GOR 218, Gravity 25.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus	PROP DEPTH	4500'	TYPE
DATE			

F.R. 1-6-66; Opr's Elev. 4378' KB
PD 4500' - SA
Contr. - Cactus
1-17-66 Drlg. 3890'.
Set 8 5/8" @ 432' W/250 sx.
1-24-66 TD 4466', PBD 4437', swbg.
Set 4 1/2" @ 4466' W/800 sx.
Perf 4205-07', 4213-15', 4237-39', 4248-
50', 4252-54', 4257-58', 4267-69', 4272-
73', 4276-77', 4288-89', 4293-94', 4299-
4301', 4305-06', 4311-13', 4320-21', 4324-
25', 4329-32' W/2 SPF
Ac (4205-4332') 2000 gals
Swbd 63 BLW, w/show oil & gas/5 hrs

1-31-66 TD 4466', PBD 4437', pmpg load.
Frac (4205-4332') 30,000 gals oil +
30,000# sd. AIR 25.5 BPM
Pmpd 154 BLO/44 hrs.

2-7-66 TD 4466', PBD 4437', pmpg load.
Ac (4205-4332') 2000 gals.
Swbd 59 BLO + 35 BAW/12 hrs.

2-14-66 TD 4466', PBD 4437', pmpg load.
Pmpd 64 BLO/29 hrs.

2-21-66 TD 4466', PBD 4437', COMPLETED.
LOG TOP: San Andres 3448'.