

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT THIS APPLICATION
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM 0108997(A)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Pan American Petroleum Corp.</i>	8. FARM OR LEASE NAME <i>J.F. FARRELL-USA</i>
3. ADDRESS OF OPERATOR <i>Box 68 Hobbs, N.M. 88240</i>	9. WELL NO. <i>6</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL x 660' FEL, Sec. 28, (UNIT P, SE/4 SE/4)	10. FIELD AND POOL, OR WILDCAT <i>CHAVEEROO SAN ANDRES</i>
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>28-7-35 NMPM</i>
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 4422' R.D.B.	12. COUNTY OR PARISH <i>ROOSEVELT</i>
	13. STATE <i>N.M.</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT ☐
(Other) <i>Completion Operation</i> ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On 12-14-65, 4 1/2" OD 9.5# J-55 Casing was set at 4462'(TD) w/ 500# 12% Gel Incor + 300# Incor neat. Tested casing w/ 1600 psi for 30 minutes. Test O.K. PBD-4428' Perforated intervals 4271-72, 74-75; 82-83; 84-86; 90-92; 4299-4300; 04-05; 13-14, 18-29, 36-38; 42-44; 84-85; 95-97; 4400-01; 05-06 w/ 2.5 SPF. Acidized w/ 2000 gal. & Traced w/ 30,000 gal. oil & 45,000# sand + 3000# glass beads. Swabbed in and evaluated.

On PT. flowed 224 BO x OBW in 24 hours thru 1 1/4" choke. TPF 75. Cgr. 25° GOR NA.

18. I hereby certify that the foregoing is true and correct.
Original Signed by:

SIGNED V. E. STALEY TITLE Area Supt

DATE 12-27-65

(This space for Federal or State office use)

0-4-USGS
1-JWB
1-SUP
1-R&Y
APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

2-Champain Ples Co. Box 1747, Midland

1-Warren Amer Oil Co, 424, 1st State Bank Bldg Midland

1-Kern Oil Land Co 418 " "

3-Tom Brown Oil Co, Box 513, Midland

*See Instructions on Reverse Side