

OPR	MIDWEST OIL CORPORATION				MAP
6 Morgan-Federal Tract I					
Sec. 27, T-7-S, R-33-E				CO-ORD	
1980' FSL, 660' FEL of Sec.					
Spd 1-17-66		CLASS		EL	
Cmp 2-20-66		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
8 5/8" 357' 300					
5 1/2" 4426' 225					
LOGS EL GR RA IND HC A					
		TD 4426', PBD 4387'			

IP San Andres Perfs 4211-87' Flwd 75 BOPD. Pot. Based on 24 hr test thru 16/64" chke., TP 100#, gravity 24., GOR 300.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4500'	TYPE
DATE		

F.R. 1-20-66
PD 4500' - SA

1-24-66 Drlg. 4296' dolo.

1-31-66 TD 4426', PBD 4387', prep to swab.
Perf @ 4211', 4223', 4238', 4245', 4257',
4261', 4267', 4280';
Ac (4211-80') 1500 gals.
Frac (4211-80') 20,000 gals cil +
20,000# sd.

2-7-66 TD 4426', PBD 4387', SI.
Swbd dry (4211-80')
Had sand block
Ac (4211-80') 1000 gals.
Swbd 44 BLO/12 hrs.

2-14-66 TD 4426', PBD 4387', swbg load.
Perf @ 4255', 4260', 4266', 4282',
4287' W/1 SPI
Ac (4211-4287') 5000 gals.
Frac (4211-4287') 15,000 gals oil +
15,000# sd.
Swbd 180 ELO/16 hrs.
2-21-66 TD 4426', PBD 4387', prep to potential.
Flwd 75 BO in 24 hrs.
2-28-66 TD 4426', PBD 4387', COMPLETED.
LOG TOPS: Anhydrite 1701', Yates 2214',
San Andres 3432', Slaughter 4103'.