

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.

NEW MEXICO DEC 2 10 45 AM '65 CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
Fee	

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT -" (Form C-101) for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
3. Address of Operator		9. Well No.
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM		Wildcat
THE <u>West</u> LINE, SECTION <u>3</u> TOWNSHIP <u>8-S</u> RANGE <u>34-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
<u>4289'</u> (GR)		<u>Roosevelt</u>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 360'
Spudded 9 7/8" Hole at 4:00 P. M. November 30, 1965

Ran 346' of 7 5/8" O. D. Casing, 15.28 LB, Spiral Weld, NEW, and cemented at 360' with 200 Sx. Incor neat with 1% CACL. Plug at 320'. Cement Circulated.

Temperature of mixing slurry 90°, Strength 12 Hours, 1000 P. S. I.
Bottom Hole Temperature - 60°, Job complete 6:45 A. M. Dec. 1, 1965.

Tested 7 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 9:00 P. M. to 9:30 P. M. December 1, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 10:15 P. M. to 10:45 P. M. December 1, 1965. Tested O. K. Job complete 10:45 P. M. December 1, 1965.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan Gillett TITLE Assistant District Superintendent DATE December 2, 1965

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: