

COUNTY	ROOSEVELT		FIELD	Wildcat		STATE	NM	
OPR	TEXACO INC.					MAP		
	1 Hogan, A. B.							
	Sec. 3, T-8-S, R-34-E					CO-ORD		
	660' fr N & W Lines of Sec.							
	Spd 11-30-65					CLASS	EC [REDACTED]	
	Cmp 12-31-65					FORMATION	DATUM	FORMATION
CSG & SX - TUBING								
7 5/8"	360'	200						
4 1/2"	4650'	700						
LOGS	EL	GR	RA	IND	HC	A		
					TD 4650'			

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Verna Drlg. Co. PROP DEPTH 4500' TYPE
DATE

F.R. 11-24-65
PD 4500' - SA
Contractor - Verna Drlg. Co.
12-6-65 Drlg. 4093' lm.
Set 7 5/8" @ 360' W/200 sx.
12-13-65 TD 4650', PBD 4616', MO Rig.
Cored 4435-85', rec 50' lm., w/sli bldg oil.
Cored 4485-4533', rec 48' being:
26' porous dolo., bldg oil;
22' dns dolo.
Cored 4533-83', rec 50' being:
5' porous dolo., bldg oil & wtr;
30' dns dolo., w/scatt poro streaks,
bldg oil & wtr;
10' dns dolo; 5' dolo., bldg wtr.
Cored 4583-4633', rec 50' dolo & anhy.,
w/scatt poro.
Set 4 1/2" @ 4650' W/700 sx.

ROOSEVELT Wildcat
TEXACO INC., #1 Hogan, A. B.

NM

Sec. 3-8S-34E

Page #2

12-20-65

TD 4650', PSD 4616', swbg load.
Perf @ 4436', 4466', 4474', 4478',
4485', 4517', 4522', 4533', 4541',
4549' W/1 SPI

Ac (4436-4549') 2000 gals.
Frac (4436-4549') 15,000 gals oil +
15,000# sd; IR 14 BPM.

Swbg 287 BLO + 3 BLW/15½ hrs.

1-3-66

TD 4650', PSD 4616', tstg on pump.

Pmpd 3 BLO + 6 BFW/24 hrs. (-57 BLO)

1-10-66

TD 4650', PSD 4616', TEMPORARILY ABANDONED.

Did not rec load.

LOG EGPS: San Andres 3727', Slaughter
4297'.