

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

K-1369

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER

Injector

2. Name of Operator

Murphy Operating Corporation

3. Address of Operator

P. O. Drawer 2648, Roswell, New Mexico 88202-2648

4. Well Location

Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line

Section 33 Township 7 South Range 33 East NMPM Roosevelt County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-26-90 Rig up pulling unit & SDFWE.

5-28-90 Nipple down well head, shear packer & TOH with same. lay down pick up 6 1/2" bit with csg scrapper & TIH SLM 4560' KBM. TOH lay down scrapper & bit SDFN.

5-29-90 TIH with cmt retainer to 4529', pump through retainer with 27 BBL H2O. Set retainer @ 4529'. Establish rate 2 BPM @ 2000 psi squeeze well with 200 sks class C 2% CaCl cmt walked pressure to 2700 psi. Displace with 24 BBLS H2O sting out of retainer & TOH lay down same SDFN WOC.

5-30-90 TIH tag cmt @ 4433.07' PBD TOH. Rig up logging truck & TIH with perf guns. Loggers TD 4420'. Perforate well as follows: (1JSPF) @ 4365', 4372', 4386', 4391', 4396' & 4399' TOH & rig down wireline truck.

Turn over to back of page....

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Lori Brown
Lori Brown

TITLE

Production Supervisor

DATE

6/11/90

505-623-7210
TELEPHONE NO.

TYPE OR PRINT NAME

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY

DISTRICT I SUPERVISOR

TITLE

DATE

JUN 21 1990

CONDITIONS OF APPROVAL, IF ANY:

TIH as follows:

1 Baker AD-1 packer	3.55
119 Jts 2 7/8", 6.5# J-55 Plastic coated tb	3738.94
1 2 7/8, tubing sub (D.C.)	10.10
KBM correction	10.00
20 points set packer @	<u>3762.59</u>

Rig down pulling unit & SDFN.

RECEIVED
JUN 20 1990
G.D.
HOOVER OFFICE

