

HOBBS OFFICE O. C. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM 0108997(9)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR <i>San American Petroleum Corp.</i>		8. FARM OR LEASE NAME <i>J.F. FARRELL - USA</i>	
3. ADDRESS OF OPERATOR <i>Box 68, Hobbs, New Mexico</i>		9. WELL NO. <i>13</i>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>660' FNL x 660' FWL Sec 28 (Unit D, NW 1/4 NW 1/4)</i>		10. FIELD AND POOL, OR WILDCAT <i>CHAUEROO SAN ANDRES</i>	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>28-7-33 NMPM</i>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>4425' R.D.B.</i>		12. COUNTY OR PARISH 13. STATE <i>ROOSEVELT N.M.</i>	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) <i>Completion Operations</i> ☒	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD-4448. On 2-9-66, 4 1/2" OD 9.5" J-55 casing was set at 4448' w/ 500 sq Incher 12% gel + 300 sx. neat. Tested casing w/ 1900 psi for 30 minutes. Test O.K. Surported intervals 42-46, 47, 49-51, 53-54, 62-66, 73-74, 82-84, 85-86, 90-91, 98-99, 4301-02, 08-10, 14-15, 17-18, 22-25, 72-74, 80-81, 83-84, 86-88 w/ 25PF. Acidized w/ 2000 gal. S-O-F, 30,000 gal oil, 30,000# sand + 3000# Glass beads.

On PT, well pumped 83 BO x 2 BW in 24 hours. GOR 752. Cgr 24°

*TD-4448 Comp 2/19/66
P&D-4414 12 New oil 2/11/66*

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE *Area Supv.* DATE *2-28-66*

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

APPROVED

*See Instructions on Reverse Side

FEB 28 1966

J. L. GORDON
ACTING DISTRICT ENGINEER

*1-1000
1-5000
1-2500
2-Completion
1-Washing Area
1-Kenn Co Hand
3-Ten Phases*